

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57921
 PART NUMBER: 4711-5
 PRODUCT NAME: BLACK LACQUER ENGINE PAINT CONC: (REVISED 08/02/07)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:
ADDRESS: 8010 DIXIE HWY. FLORENCE, KY 41042	HEALTH: 3	
EMERGENCY TELEPHONE NUMBER: (800)424-9300	FIRE: 3	HEALTH 3 FIRE
INFORMATION TELEPHONE NUMBER: (859) 372-5900	REACTIVITY: 2	1 2
DATE PREPARED: 07/26/06	PERSONAL PROTECTION: G	SPEC.HAZ. REACT.

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
67-63-0	2- PROPANOL					400ppm	400ppm		10-30
108-88-3	TOLUENE					100ppm	50ppm		7-13
1330-20-7	XYLENE					100ppm	100ppm		5-10
78-93-3	2- BUTANONE					200	200		3-7
67-56-1	METHYL ALCOHOL					250	200		3-7
111-76-2	ETHYLENE GLYCOL BUTYL ETHER					25ppm	25ppm		3-7

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	N/AP	SPECIFIC GRAVITY (H2O=1)	0.8576
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	NO		
APPEARANCE AND ODOR:	BLACK PAINT. SOLVENT ODOR.		
OTHER INFORMATION:	N/AP		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 25° F TCC	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA : CO 2 OR DRY CHEMICAL.		
SPECIAL FIRE FIGHTING PROCEDURES: N/AP		
UNUSUAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : N/AP
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/AP
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION .
HEALTH HAZARDS (ACUTE AND CHRONIC): EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57921

PRODUCT NAME: 4711-5 BLACK LAQUER ENGINE PAINT CONC: (REVISED: 08/02/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP CAREFULLY. FLAMMABLE

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP AWAY FROM FIRE OR FLAME.

OTHER PRECAUTIONS: N/AP

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: NORMAL

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES, RUBBER GLOVES, AND N.I.O.S.H. APPROVED ORGANIC-VAPOR RESPIRATOR IS RECOMMENDED.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: *THIS MATERIAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART 372.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = PAINT

PACKING GROUP = III

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE

N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|----------------------|----------------|
| 1. | ALIPHATIC DISTILLATE | CAS# 8032-32-4 |
| 2. | N. BUTYL ACETATE | CAS# 123-86-4 |
| 3. | 2- PROPANOL | CAS# 67-63-0 |
| 4. | TOLUENE | CAS# 108-88-3 |
| 5. | XYLENE | CAS# 1330-20-7 |

V. O. C. CONTENT: 734 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.