

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57788
 PART NUMBER: C-16
 PRODUCT NAME: POWER -SOL (REVISED 8/06/07)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY. FLORENCE, KY 41042	HEALTH: 2	<table style="border: none; margin: auto;"> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	2	3	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
2	3									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	FIRE: 3									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	REACTIVITY: 0									
DATE PREPARED: 02/23/04	PERSONAL PROTECTION: B									

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% RECOMMENDED
8052-41-3	PETROLEUM DISTILLATE					100			40-70
64742-95-6	AROMATIC HYDROCARBON					N/EST	N/EST		15-40
78-92-2	SECONDARY BUTANOL***				Y	100			3-7

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	240° F	SPECIFIC GRAVITY (H ₂ O=1)	0.8039
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	VERY LOW		
APPEARANCE AND ODOR:	CLEAR LIQUID. SOLVENT ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 72° F TCC	FLAMMABLE LIMITS: LEL: N/AV UEL: N/AV
EXTINGUISHING MEDIA: CO 2 OR DRY CHEMICAL.	
SPECIAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID.	
UNUSUAL FIRE FIGHTING PROCEDURES: NONE	

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): N/AP
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/AP
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION AND INGESTION.
HEALTH HAZARDS (ACUTE AND CHRONIC): EXCESSIVE INHALATION MAY CAUSE NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: DROWZINESS.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. IN CASE OF ACCIDENTAL INGESTION, GET MEDICAL HELP.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57788
 PRODUCT NAME: C-16 POWER-SOL (REVISED 8/06/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP SPILLED LIQUID CAREFULLY. FLAMMABLE.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID OPEN FLAME.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: NORMAL

PERSONAL PROTECTIVE EQUIPMENT: SOLVENT RESISTANT GLOVES. SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: ***THIS MATERIAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

SECONDARY BUTANOL CAS# 78-92-2 3-7%

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUID., N.O.S.
 (CONTAINS PETROLEUM SPIRITS)

PACKING GROUP = 11

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | |
|-------------------------|-----------------|
| 1. PETROLEUM DISTILLATE | CAS# 8052-41-3 |
| 2. AROMATIC HYDROCARBON | CAS# 64742-95-6 |
| 3. SECONDARY BUTANOL | CAS# 78-92-2 |

V. O. C. CONTENT: 804 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
