

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57850
 PART NUMBER: C-42
 PRODUCT NAME: WHEELIE CLEAN (REVISED 5/06/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042 EMERGENCY TELEPHONE NUMBER: (800) 424-9300 INFORMATION TELEPHONE NUMBER: (859) 372-5900 DATE PREPARED: 09/15/99	HMIS RATING: HEALTH: 2 FIRE: 1 REACTIVITY: 0 PERSONAL PROTECTION: B	NFPA RATING: <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">ALK</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	2	1	HEALTH	FIRE	ALK	0	SPEC.HAZ.	REACT.
2	1									
HEALTH	FIRE									
ALK	0									
SPEC.HAZ.	REACT.									

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
6834-92-0	SODIUM SILICATE				N/EST.	N/EST.		10

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212°	SPECIFIC GRAVITY (H ₂ O=1)	1.0800
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	>1	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	COMPLETE		
APPEARANCE AND ODOR:	DARK BLUE LIQUID WITH LIGHT ODOR.		
OTHER INFORMATION:	pH = 12.88		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/AP	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA : FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.		
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS.		
UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57850
 PRODUCT NAME : C-42 WHEELIE CLEAN (REVISED 5/06/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSOL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: CHEMICAL RUBBER GLOVES AND SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CORROSIVE LIQUID, N.O.S.
 (CONTAINS SODIUM SILICATE)

PACKAGING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-----------------|----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | SODIUM SILICATE | CAS# 6834-92-0 |
| 3. | SURFACTANT | MIXTURE |
| 4. | DYE | MIXTURE |

V. O. C. CONTENT: 0 GRAMS PER LITER