

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57888
 PART NUMBER: C-62
 PRODUCT NAME: CAL-SOLV (REVISED 5/06/08)
 CHEMICAL:

SECTION I

| | | | | | | | | | | |
|---|--|---|--------|---|--------|------|---|---|-----------|--------|
| MANUFACTURER: BAF INDUSTRIES | HMIS RATING: HEALTH: 1 FIRE: 3 REACTIVITY: 0 PERSONAL PROTECTION: B | NFPA RATING: <div style="text-align: center;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="border: none;">1</td> <td style="border: none;">3</td> </tr> <tr> <td style="border: none;">HEALTH</td> <td style="border: none;">FIRE</td> </tr> <tr> <td style="border: none;">0</td> <td style="border: none;">0</td> </tr> <tr> <td style="border: none;">SPEC.HAZ.</td> <td style="border: none;">REACT.</td> </tr> </table> </div> | 1 | 3 | HEALTH | FIRE | 0 | 0 | SPEC.HAZ. | REACT. |
| 1 | | | 3 | | | | | | | |
| HEALTH | | | FIRE | | | | | | | |
| 0 | | | 0 | | | | | | | |
| SPEC.HAZ. | | | REACT. | | | | | | | |
| ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042 | | | | | | | | | | |
| EMERGENCY TELEPHONE NUMBER: (800) 424-9300 | | | | | | | | | | |
| INFORMATION TELEPHONE NUMBER: (859) 372-5900 | | | | | | | | | | |
| DATE PREPARED: 05/14/07 | | | | | | | | | | |

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

| CAS NUMBER | HAZARDOUS COMPONENT | NTP | IARC | SUB-PART/Z | SARA 313 | OSHA PEL | ACGIH TLV | OTHER LIMITS RECOMMENDED | % |
|------------|-----------------------|-----|------|------------|----------|----------|-----------|--------------------------|-------|
| 64742-89-8 | ALIPHATIC HYDROCARBON | | | | | 100ppm | 100ppm | | 30-60 |
| 67-64-1 | ACETONE | | Y | | Y | 750ppm | 750ppm | | 15-40 |
| 64742-47-8 | ALIPHATIC HYDROCARBON | | | | | N/EST | N/EST | | 10-30 |
| 112-34-5 | GLYCOL ETHER | | | | | N/EST | N/EST | | 1-5 |

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

| | | | |
|-------------------------|---------------------------------|---------------------------------------|--------|
| BOILING POINT | N/AV | SPECIFIC GRAVITY (H ₂ O=1) | 0.7655 |
| VAPOR PRESSURE (mm Hg.) | N/AV | MELTING POINT | N/AP |
| VAPOR DENSITY (AIR = 1) | N/AV | EVAPORATION RATE (Butyl Acetate = 1) | N/AV |
| SOLUBILITY IN WATER: | MISCIBLE | | |
| APPEARANCE AND ODOR: | CLEAR LIQUID WITH SOLVENT ODOR. | | |
| OTHER INFORMATION: | NONE | | |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| | | |
|--|-----------------------------|-----------|
| FLASH POINT: -4° F | FLAMMABLE LIMITS: LEL: N/AV | UEL: N/AV |
| EXTINGUISHING MEDIA : FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER. | | |
| SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS. | | |
| UNUSUAL FIR FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE. | | |

SECTION V - REACTIVITY DATA

| |
|--|
| STABILITY: STABLE |
| INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS. |
| HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES. |
| HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. |

SECTION VI - HEALTH HAZARD DATA

| |
|--|
| ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION. |
| HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN. EXCESSIVE INHALATION MAY CAUSE DIZZINESS OR NAUSEA. |
| SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE. |
| MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN. |
| EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTONS PERSIST, GET MEDICAL ATTENTION. |
| OTHER HEALTH WARNINGS: NONE |

MSDS NUMBER: 57888
PRODUCT NAME : C-62 CAL-SOLV (REVISED 5/06/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM
FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: CORROSIVE & FLAMMABLE LIQUID.

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: CHEMICAL RUBBER GLOVES AND SAFETY GLASSES

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUIDS N.O.S.
(CONTAINS ACETONE AND ALIPHATIC HYDROCARBON)
UN-1993

PACKAGING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-----------------------|-----------------|
| 1. | ALIPHATIC SOLVENT | CAS# 64742-89-8 |
| 2. | ACETONE | CAS# 67-64-1 |
| 3. | ALIPHATIC HYDROCARBON | CAS# 64742-47-8 |
| 4. | GLYCOL ETHER | CAS# 112-34-5 |

V. O. C. CONTENT: 321 GRAMS PER LITER