

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57839
 PART NUMBER: C-83
 PRODUCT NAME: X TRACT POWER (REVISED 8/07/07)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:			
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042			HEALTH: 1	1	0
EMERGENCY TELEPHONE NUMBER: (800) 424-9300			FIRE: 0	HEALTH	FIRE
INFORMATION TELEPHONE NUMBER: (859) 372-5900			REACTIVITY: 0	0	0
DATE PREPARED: 02/22/05			PERSONAL PROTECTION: B	SPEC.HAZ.	REACT.

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC SUB-	SARA	OSHA PEL	ACGIH TLV	OTHER LIMITS	%
								RECOMMENDED

NONE

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H ₂ O=1)	1.0235
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	>1	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	COMPLETE		
APPEARANCE AND ODOR:	CLEAR AMBER LIQUID WITH MILD ODOR.		
OTHER INFORMATION:	pH = 12.30		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/AP	FLAMMABLE LIMITS:	LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA : FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.			
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS.			
UNUSUAL FIRE FIHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.			

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION, INGESTION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, IRRITATION TO UPPER RESPRIATORY TRACT, HARMFUL IF SWALLOWED.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57839
PRODUCT NAME : C-83 X TRACT POWER (REVISED 8/07/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES, CHEMICAL SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CLEANING LIQUID.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|------------|----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | SURFACTANT | MIXTURE |
| 3. | PERFUME | MIXTURE |
| 4. | DYE | MIXTURE |

V. O. C. CONTENT: 2 GRAMS PER LITER