

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57816
 PART NUMBER: P-27
 PRODUCT NAME: ULTIMATE CUTTER & SCRATCH REMOVER (REVISED 5/06/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:
ADDRESS: 8010 DIXIE3 HWY FLORENCE, KY 41042	HEALTH: 1	
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	FIRE: 2	
INFORMATION TELEPHONE NUMBER: (859) 372-5900	REACTIVITY: 0	
DATE PREPARED: 05/02/07	PERSONAL PROTECTION: B	

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
1344-28-1	ALUMINUM OXIDE	N	N	N	N	10mg/m3	10mg/m3		10-30
8052-41-3	PETROLEUM DISTILLATE					100ppm	100ppm		10-30
64742-47-8	ALIPHATIC PETROLEUM DISTILLATES					N/AV	N/AV		10-30
14808-60-7	MICROCRYSTALLINE SILICA*	Y	N	Y	N	10mg/m3	0.1mg/m3		7-13

* (SEE SECTION IX)

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	N/AV	SPECIFIC GRAVITY (H2O=1)	1.1399
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	THICK OPAQUE LIQUID WITH SOLVENT SMELL.		
OTHER INFORMATION:	pH = 8.70		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 104 °F	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: CO 2, WATER FOG, DRY CHEMICAL, REGULAR FOAM.		
SPECIAL FIRE FIGHTING PROCEDURES: SCBA RECOMMENDED.		
UNUSUAL FIRE FIGHTING PROCEDURES: NONE KNOWN		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : NONE KNOWN.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN. EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57816
 PRODUCT NAME: P-27 ULTIMATE CUTTER & SCRATCH REMOVER (REVISED 5//06/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: TAKE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH STATE , LOCAL AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL

PERSONAL PROTECTIVE EQUIPMENT: CHEMICAL RUBBER GLOVES AND SAFETY GLASSES. A NIOSH APPROVED DUST MASK IS RECOMMENDED WHEN BUFFING THIS PRODUCT.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: * THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION, IARC HAS CLASSIFIED INHALATION OF CS AS A CARCINOGENIC FOR HUMANS (GROUP 1). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. INHALATION OF CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NON CANCEROUS LUNG DISEASE.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = COMBUSTIBLE LIQUID, N.O.S.
 (CONTAINS PETROLEUM SPIRIT)

PACKING GROUP = 111

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

1.	WATER	CAS# 7732-18-5
2.	ALUMINUM OXIDE	CAS# 1344-28-1
3.	PETROLEUM DISTILLATE	CAS# 8052-41-3
4.	ALIPHATIC PETROLEUM DISTILLATES	CAS# 64742-47-8
5.	MICROCRYSTALLINE SILICA	CAS# 14808-60-7

V. O. C. CONTENT: 153 GRAMS PER LITER
