

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER : 57514
 PART NUMBER: P-33
 PRODUCT NAME: TROUBLESHOOTER (REVISED 5/07/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	1	2	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	2									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	PERSONAL PROTECTION: B									
DATE PREPARED: 09/06/06										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-	SARA	OSHA	PEL	ACGIH	TLV	OTHER LIMITS	%
				PART/Z	313					RECOMMENDED	
64742-47-8	ALIPHATIC PETROLEUM DISILLATES					N/EST.		N/EST.			10-30
68855-54-9	FLUX CALCINED DIATOMACEOUS EARTH *	N	N	N	N	5mg/m3		10mg/m3			5-10
	* (SEE SECTION IX)										

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	N/AV	SPECIFIC GRAVITY (H2O=1)	0.9695
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AV
VAPOR DENSITY (AIR = 1)	HEAVIER	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	LIGHT ORANGE LIQUID WITH MILD ODOR.		
OTHER INFORMATION:	pH = 8.52		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 140° F TCC	FLAMMABLE LIMITS: LEL: N/AV UEL: N/AV
EXTINGUISHING MEDIA: CO 2, WATER FOG, DRY CHEMICAL, REGULAR FOAM.	
SPECIAL FIRE FIGHTING PROCEDURES: SCBA RECOMMENDED.	
UNUSUAL FIRE FIGHTING PROCEDURES: NONE KNOWN	

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : NONE KNOWN.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN; INHLATION MAY CAUSE IRRITATION AND SORENESS IN THROAT & NOSE.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF IRRITATION PERSISTS, SEEK MEDICALADVICE.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57574
 PRODUCT NAME: P-33 TROUBLESHOOTER (REVISED 5/07/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: TAKE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL STATE, LOCAL, AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: NORMAL

PERSONAL PROTECTIVE EQUIPMENT: CHEMICAL RUBBER GLOVES AND SAFETY GLASSES. A NIOSH APPROVED DUST MASK IS RECOMMENDED WHEN BUFFING THIS PRODUCT.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: * THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED INHALATION OF CS AS CARCINOGENIC FOR HUMANS (GROUP 1). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. INHALATION OF CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.

CRISTOBALITE CAS# 14464-46-1 <6% QUARTZ CAS# 14808-60-7 <3%

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = COMBUSTIBLE LIQUID, N.O.S.
 (CONTAINS PETROLEUM SPIRITS)

PACKING GROUP = III

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE

N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|----------------------------------|-----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | ALIPHATIC PETROLEUM DISTILLATE | CAS# 64742-47-8 |
| 3. | FLUX CALCINED DIATOMACEOUS EARTH | CAS# 58855-54-9 |
| 4. | WHITE MINERAL OIL | CAS# 8042-47-5 |
| 5. | SILICONE | CAS# 63148-62-9 |

V.O.C. CONTENT: 1 GRAM. PER LITER.
