

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57809
 PART NUMBER: P-35-H
 PRODUCT NAME: SATIN CRÈME WAX™ (REVISED 5/06/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	1	2	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	2									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	PERSONAL PROTECTION: B									
DATE PREPARED: 03/22/07										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP IARC SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
64742-47-8	ALIPHATIC HYDROCARBONS			N/EST	N/EST		10-30
8052-41-3	ALIPHATIC PETROLEUM DISTILLATES			100ppm	100ppm		10-30
66402-68-4	CALCINED KAOLIN CLAY			5mg/m3	5mg/m3		7-13

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H2O=1)	0.9515
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	LIGHT YELLOW EMULSION.		
OTHER INFORMATION:	pH= 9.10		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 113° F	FLAMMABLE LIMITS: LEL: N/AV UEL: N/AV
EXTINGUISHING MEDIA: CO 2, WATER FOG, DRY CHEMICAL, REGULAR FOAM.	
SPECIAL FIRE FIGHTING PROCEDURES: SCBA RECOMMENDED.	
UNUSUAL FIRE FIGHTING PROCEDURES: NONE KNOWN.	

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : STRONG OXIDIZERS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA..
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTONS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE.

MSDS NUMBER: 57809
PRODUCT NAME: P-35-H SATIN CRÈME WAX™ (REVISED 5/06/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL

PERSONAL PROTECTIVE EQUIPMENT: CHEMICAL RUBBER GLOVES AND SAFETY GLASSES. A NIOSH APPROVED DUST MASK IS RECOMMENDED WHEN BUFFING THIS PRODUCT.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = COMBUSTIBLE LIQUID, N.O.S.
(CONTAINS PETROLEUM DISTILLATES)

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | |
|------------------------------------|-----------------|
| 1. WATER | CAS# 773218-5 |
| 2. ALIPHATIC HYDROCARBONS | CAS# 64742-47-8 |
| 3. ALIPHATIC PETROLEUM DISTILLATES | CAS# 8052-41-3 |
| 4. CALCINED KOALIN CLAY | CAS# 66402-68-4 |
| 5. SURFACTANT & PERFUME | MIXTURE |

V. O. C. CONTENT: 138 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN ;CARCINOGEN AS SET FORTH BY I.A.R.C. OR OTHER REGULATORY AGENCY.
