

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57518
 PART NUMBER: P-38
 PRODUCT NAME: RV, BOAT & AIRCRAFT WAX (REVISED 5/07/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	1	2	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	2									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	PERSONAL PROTECTION: B									
DATE PREPARED: 12/08/05										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
8052-41-3	STODDARD SOLVENT			Y		100ppm	100ppm		10-30
64742-47-8	ALIPHATIC PETROLEUM DISTILLATES					400ppm			5-10
68855-54-9	DIATOMACEOUS EARTH**					5mg/m3	5mg/m3		5-10

** SEE SECTION IX

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212°F	SPECIFIC GRAVITY (H ₂ O=1)	0.9935
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	PINK EMULSION WITH SOLVENT ODOR.		
OTHER INFORMATION:	N/AP		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 107°F	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.		
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS.		
UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57518
 PRODUCT NAME: P-38 RV, BOAT & AIRCRAFT WAX (REVISED 5/07/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING. KEEP AWAY FROM FLAME.

OTHER PRECAUTIONS: NONE.

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES AND SAFETY GLASSES. A NIOSH APPROVED DUST MASK IS RECOMMENDED WHEN BUFFING THIS PRODUCT.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: *THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION, IARC HAS CLASSIFIED INHALATION OF CS AS CARCINOGENIC FOR HUMANS (GROUP 1). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN, INHALATION OF CS IS ALSO A KNOWN CAUSE OF SILICISIS, A NONCANCEROUS LUNG DISEASE.

**DIATOMACEOUS EARTH MAY CONTAIN QUARTZ CAS# 61790-53-2 CRISTOBALITE CAS# 14464-46-1

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = COMBUSTIBLE LIQUID, N.O.S.
 (CONTAINS PETROLEUM SPIRITS)

PACKING GROUP = III

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE

N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | |
|------------------------------------|-----------------|
| 1. WATER | CAS# 7732-18-5 |
| 2. STODDARD SOLVENT | CAS# 8052-41-3 |
| 3. ALIPHATIC PETROLEUM DISTILLATES | CAS# 64742-47-8 |
| 4. DIATOMACEOUS EARTH | CAS# 61790-53-2 |
| 5. DIMETHYLPOLYSILOXANES | CAS# 63148-62-9 |

V.O.C. CONTENT: 134 GRAMS PER LITER
