

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER 57842
 PART NUMBER: R-79
 PRODUCT NAME: QUICKOR WAX (REVISED 5/07/08)
 CHEMICAL:

SECTION I

| | | | | | | | | | | |
|---|------------------------|---|---|---|--------|------|---|---|-----------|--------|
| MANUFACTURER: BAF INDUSTRIES | HMIS RATING: | NFPA RATING: | | | | | | | | |
| ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042 | HEALTH: 1 | <table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table> | 1 | 2 | HEALTH | FIRE | 0 | 0 | SPEC.HAZ. | REACT. |
| 1 | 2 | | | | | | | | | |
| HEALTH | FIRE | | | | | | | | | |
| 0 | 0 | | | | | | | | | |
| SPEC.HAZ. | REACT. | | | | | | | | | |
| EMERGENCY TELEPHONE NUMBER: (800) 424-9300 | REACTIVITY: 0 | | | | | | | | | |
| INFORMATION TELEPHONE NUMBER: (859) 372-5900 | PERSONAL PROTECTION: B | | | | | | | | | |
| DATE PREPARED: 12/05/05 | | | | | | | | | | |

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

| CAS NUMBER | HAZARDOUS COMPONENT | NTP IARC SUB-PART/Z | SARA 313 | OSHA PEL | ACGIH TLV | OTHER LIMITS RECOMMENDED | % |
|------------|---|---------------------|----------|---------------------------------|-----------|--------------------------|-------|
| 64742-47-8 | ALIPHATIC HYDROCARBON | | | N/EST | N/EST | | 10-30 |
| 8052-41-3 | PETROLEUM DISTILLATE | | | 300ppm | 300ppm | | 10-30 |
| 66402-68-4 | KAOLIN CLAY * (SEE SECTION IX) ** (SEE SECTION IX) | | | 5 mg/m3 (RESP DUST 8HR. TWA) | 5 mg/m3 | | 7-13 |

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

| | | | |
|-------------------------|--------------------------------|---------------------------------------|--------|
| BOILING POINT | 212° F | SPECIFIC GRAVITY (H ₂ O=1) | 0.9095 |
| VAPOR PRESSURE (mm Hg.) | N/AV | MELTING POINT | N/AP |
| VAPOR DENSITY (AIR = 1) | N/AV | EVAPORATION RATE (Butyl Acetate = 1) | N/AV |
| SOLUBILITY IN WATER: | MISCIBLE. | | |
| APPEARANCE AND ODOR: | YELLOW EMULSION. SOLVENT ODOR. | | |
| OTHER INFORMATION: | pH=9.79 | | |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| | | | |
|--|-------------------|-----------|-----------|
| FLASH POINT: 109° F | FLAMMABLE LIMITS: | LEL: N/AV | UEL: N/AV |
| EXTINGUISHING MEDIA: CO 2 OR DRY CHEMICAL. | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: NONE | | | |
| UNUSUAL FIRE FIGHTING PROCEDURES: NONE | | | |

SECTION V - REACTIVITY DATA

| |
|---|
| STABILITY: STABLE |
| INCOMPATIBILITY (MATERIALS TO AVOID) : N/AP |
| HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/AP |
| HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. |

SECTION VI - HEALTH HAZARD DATA

| |
|--|
| ROUTE(S) OF ENTRY: INGESTION |
| HEALTH HAZARDS (ACUTE AND CHRONIC): NONE |
| SIGNS AND SYMPTOMS OF EXPOSURE: NONE. |
| MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE |
| EMERGENCY AND FIRST AID PROCEDURES: FOR ACCIDENTAL INGESTION, GET MEDICAL AID. |
| OTHER HEALTH WARNINGS: N/AP |

MSDS NUMBER: 57842
 PRODUCT NAME: R-79 QUICKOR WAX (REVISED 5/07/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP SPILLED LIQUID.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING

OTHER PRECAUTIONS: N/AP

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: NONE

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES AND GLOVES. A N.I.O.S.H. APPROVED DUST MASK IS RECOMMENDED WHEN BUFFING THIS PRODUCT

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: ** THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED INHALATION OF CS AS CARCINOGENIC FOR HUMANS (GROUP I). CS IS LISTED BY NTP AS A SUBSTANCE WHICH MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. INHALATION OF CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.

* KAOLIN CLAY MAY CONTAIN <1% QUARTZ CAS# 014808-60-7

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CONSUMER COMMODITY ORM-D

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

| | | |
|----|-----------------------|-----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | ALIPHATIC HYDROCARBON | CAS# 64742-47-8 |
| 3. | PETROLEUM DISTILLATE | CAS# 64742-89-8 |
| 4. | KAOLIN CLAY | CAS# 6402-68-4 |
| 5. | DYE & PERFUME | MIXTURE |

V. O. C. CONTENT: 133 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
