

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57787
 PART NUMBER: S-94
 PRODUCT NAME: WET LOOK (REVISED 3/14/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	1 3
EMERGENCY TELEPHONE NUMBER: (800)424-9300	FIRE: 3	HEALTH FIRE
INFORMATION TELEPHONE NUMBER: (714)540-3850	REACTIVITY: 0	0 0
DATE PREPARED: 04/04/06	PERSONAL PROTECTION: B	SPEC.HAZ. REACT.

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% RECOMMENDED
142-82-5	ALIPHATIC HYDROCARBON	N	N			400ppm	1640mg/m3		60-100

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	149-159° F	SPECIFIC GRAVITY (H ₂ O=1)	0.7127
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	INSOLUBLE		
APPEARANCE AND ODOR:	BLUE LIQUID. SOLVENT ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 15°F TCC	FLAMMABLE LIMITS: LEL: 1.0%	UEL: N/AV
EXTINGUISHING MEDIA : CO 2 OR DRY CHEMICAL.		
SPECIAL FIRE FIGHTING PROCEDURES: SCBA RECOMMENDED.		
UNUSUAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID. VAPORS MAY TRAVEL.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : STRONG OXIDIZERS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO AND CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION, SKIN
HEALTH HAZARDS (ACUTE AND CHRONIC): EXCESSIVE INHALATION MAY CAUSE DIZZINESS AND NAUSEA. MAYN CAUSE REDDENING OF SKIN.
SIGNS AND SYMPTOMS OF EXPOSURE: NAUSEA, DIZZINESS. REDDENING AND BURNING SENSATION ON SKIN.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: MOVE TO FRESH AIR, FLUSH WITH PLENTY OF WATER
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57787
PRODUCT NAME: S-94 WET LOOK (REVISED 3/14/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: TAKE UP WITH NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP AWAY FROM SPARKS OR OPEN FLAME.

OTHER PRECAUTIONS: FLAMMABLE LIQUID AND VAPORS.

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL / LOCAL EXHAUST.

PERSONAL PROTECTIVE EQUIPMENT: SOLVENT RESISTANT GLOVES AND SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUID, N.O.S.
(CONTAINS ALIPHATIC HYDROCARBON)
UN-1993

PACKING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-----------------------|-----------------|
| 1. | ALIPHATIC HYDROCARBON | CAS# 142-82-5 |
| 2. | DIMETHYLPOLYSILOXANES | CAS# 63148-62-9 |
| 3. | DYE AND PERFUME | MIXTURE |

V. O. C. CONTENT: 598 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
