

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57719
 PART NUMBER: UB-82
 PRODUCT NAME: ULTRA BASE VINYL & TIRE DRESSING (REVISED 8/07/07)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="border: 1px dashed black; margin: auto;"> <tr> <td style="padding: 5px;">1</td> <td style="padding: 5px;">0</td> </tr> <tr> <td style="padding: 5px;">HEALTH</td> <td style="padding: 5px;">FIRE</td> </tr> <tr> <td style="padding: 5px;">0</td> <td style="padding: 5px;">0</td> </tr> <tr> <td style="padding: 5px;">SPEC.HAZ.</td> <td style="padding: 5px;">REACT.</td> </tr> </table>	1	0	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	0									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (714) 540-3850	PERSONAL PROTECTION: A									
DATE PREPARED: 11/25/03										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-	SARA	OSHA	PEL	ACGIH	TLV	OTHER LIMITS	%
											RECOMMENDED

NONE

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H ₂ O=1)	1.0019
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AV
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	WHITE EMULSION WITH FRAGRANCE SMELL		
OTHER INFORMATION:	pH= 9.25		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: N/AP		
SPECIAL FIRE FIGHTING PROCEDURES: SCBA RECOMMENDED.		
UNUSUAL FIRE FIGHTING PROCEDURES: NONE KNOWN.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID) : NONE KNOWN.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO₂.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES.

HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN.

SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR, FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.

OTHER HEALTH WARNINGS: NONE

PRODUCT NAME: UB-82 ULTRA BASE VINYL & TIRE DRESSING (REVISED 8/07/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL.

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CLEANING LIQUID.

PACKING GROUP = N/AP

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE

N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | |
|-----------------------------|-----------------|
| 1. POLYDIMETHYLSILOXANE | CAS# 63148-62-9 |
| 2. WATER | CAS# 7732-18-5 |
| 3. SURFACTANT | MIXTURE |
| 4. SODIUM XYLENE SURFACTANT | CAS# 1300-72-7 |
| 5. PERFUME | MIXTURE |

V. O. C. CONTENT: 0 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
