

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57523
 PART NUMBER: W-41
 PRODUCT NAME: YELLOW WAX (REVISED 12/03/07)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="border: 1px dashed black; width: 100px; height: 100px; margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	1	2	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	2									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	PERSONAL PROTECTION: A									
DATE PREPARED: 05/25/05										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC SUB-	SARA	OSHA PEL	ACGIH TLV	OTHER LIMITS %
				PART/Z			RECOMMENDED
64742-47-8	ALIPHATIC SOLVENT			313	N/EST	N/EST	60-100

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	330° F	SPECIFIC GRAVITY (H ₂ O=1)	0.8099
VAPOR PRESSURE (mm Hg.)	N/AP	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AP	EVAPORATION RATE (Butyl Acetate = 1)	N/AP
SOLUBILITY IN WATER:	NONE		
APPEARANCE AND ODOR:	YELLOW PASTE. SOLVENT ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 140° F PMCC	FLAMMABLE LIMITS: LEL: N/AV UEL: N/AV
EXTINGUISHING MEDIA: CO 2 OR DRY CHEMICAL.	
SPECIAL FIRE FIGHTING PROCEDURES: N/AP	
UNUSUAL FIRE FIGHTING PROCEDURES: N/AP	

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): N/AP
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/AP
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: NONE.
HEALTH HAZARDS (ACUTE AND CHRONIC): NONE
SIGNS AND SYMPTOMS OF EXPOSURE: NONE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE
EMERGENCY AND FIRST AID PROCEDURES: N/AP.
OTHER HEALTH WARNINGS: N/AP

MSDS NUMBER: 57523
PRODUCT NAME: W-41 YELLOW WAX (REVISED 12/03/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP. COMBUSTIBLE.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: N/AP.

OTHER PRECAUTIONS: N/AP

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: NORMAL

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = COMPOUND POLISHING PASTE.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-------------------|-----------------|
| 1. | ALIPHATIC SOLVENT | CAS# 64742-47-8 |
| 2. | POLYSILOXANE | CAS# 63148-62-9 |
| 3. | WAX | MIXTURE |
| 4. | PERFUME | MIXTURE |
| 5. | DYE | MIXTURE |

PERCENT VOLATILE ORGANIC COMPOUNDS BY WEIGHT DOES NOT EXCEED 2%
