



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- **Semi-Gloss Lacquer Paint**
- **Fast Drying Formula**
- **Concentrated 2-to-1 For Economy**
- **Renews Factory Appearance**

- **Apply With Conventional Spray Equipment**
- **For Engines, Fender Wells & More**
- **Will Not Crack, Chip or Peel**

4711-5 **BLACK LACQUER ENGINE PAINT CONCENTRATE**

FEATURES AND BENEFITS

A durable, semi-gloss black lacquer engine paint that is concentrated (2:1) for the utmost in quality as well as economy. Fast-drying and heat resistant, its rich, solid pigmentation formula provides excellent coverage and adhesion to all pre-cleaned metal and rubber surfaces. Renews the appearance of engine compartments and hoses, belts, cables, wires, distributors, radiators, fire walls, tires, fender wells, tools, equipment, machinery, rubber floor mats and more. Lays down a semi-gloss coating that provides long lasting beauty and protection. Creates that "fresh from the factory" look. 4711 will not crack, chip or peel. Mixes easily with lacquer thinner for a cost effective black paint. Apply with pistol sprayer, pressure pot (Sure Shot™) or any conventional spray equipment.

RECOMMENDED FOR

Renews the appearance of engine compartments and hoses, belts, cables, wires, distributors, radiators, fire walls, tires, fender wells, tools, equipment, machinery, rubber floor mats and more. Lays down a semi-gloss coating that provides long lasting beauty and protection.

APPLICATION

Directions: Shake well before using. For your protection, safety glasses and rubber gloves are recommended while using this product. Keep container closed when not in use. For best results, area to be coated should be clean and free of dirt & grease. Pre-clean engine compartment with PRO® C-51 Red Devil™ Engine Degreaser. Allow to dry completely. Smooth rust and rough areas with wire

brush or steel wool. Mix one (1) part 4311 Black lacquer Engine Paint with up to two (2) parts lacquer thinner for normal conditions. Hard to cover areas may require a stronger concentration of paint. **NOTE: FLAMMABLE LIQUID-DO NOT APPLY ONTO HOT SURFACE.** Apply with pistol sprayer, pressure pot (Sure Shot™) or any conventional spray equipment (35-40 psi air pressure). Apply in even thin coats rather than one heavy application. Spray diluted product onto clean, dry surface and allow to dry for approximately 10 minutes. Repeat as necessary.

SPECIAL NOTES

For short cuts on engine compartment painting, spot paint areas where chipped, stained or rusted.

PACKAGING

5 GALLON PAIL