



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- **Spray On, Rinse Off**
- **Great for Car Washes**
- **Designed to Remove Brake Dust, Road Grime, Dressing, Dirt & Grease**
- **Ready to Use, Non Caustic Formula**

- **Safely Cleans Painted, Clearcoated Aluminum, Powdercoated, Mags, Chrome & Wire Wheels**
- **VOC Compliant**

C-41 **NON-ACID WHEEL CLEANER**

FEATURES AND BENEFITS

C-41 Non-Acid Wheel Cleaner proves that you can get high performance from non-acid cleaners. C-41 is a strong, fast acting cleaner designed to quickly remove brake dust, metallic particulates, dirt, oil, grease and other surface contaminants from all types of OEM (Original Equipment Manufacturer) or factory wheels. Its non-caustic formulation safely cleans painted and/or clearcoated aluminum, powder coated, mags, chrome and wire wheels as well as plastic hubcaps. By the way, almost all OEM wheels are clearcoated, even if they are painted or polished. C-41 is quick and easy to use. Simply spray on and rinse off. It contains no harmful solvents, caustic cleaners or dangerous acids that could be hazardous to wheels as well as users of the product. C-41 is environmentally friendly, safe and easy to use, giving you peace of mind when you put it in the hands of your employees. This one-step solution, cleans and brightens with it's unique formula that incorporates a buffering component to protect wheels as well as a special flow agent that helps it to rinse spot free. Additionally, it cleans tires and whitewalls, so you don't have to use two different products to get the job done. Wheels should be cleaned and polished regularly. If not removed, road salts and metallic

particulates in brake dust can accelerate the corrosion process and damage wheels. C-41 is safe and can be used regularly on all types of OEM wheel finishes and hubcaps.

RECOMMENDED FOR

C-41 is the perfect cleaner for all types of OEM (Original Equipment Manufacturer) or factory wheels.....painted and/or clearcoated aluminum, powder coated, mags, alloy, chrome and wire wheels as well as plastic hubcaps. It also cleans tires and whitewalls. Note: Not recommended for certain aftermarket wheel finishes such as non-coated, polished, anodized or polished billet aluminum.

APPLICATION

Note: Always clean your wheels & tires first before washing and waxing your vehicle. That way you won't be splashing water or getting cleaner on your freshly waxed finish.

Directions: Shake well before using. For your protection, safety glasses and rubber gloves are recommended while using this product. **Do not apply C-41 to a hot surface or let dry on surface.** Avoid contact with the painted vehicle finish. Cool wheels with cold water rinse before applying product. Clean one wheel at a time. Spray C-41 onto wheel

and allow to soak 30-60 seconds. Agitate lightly with brush or sponge on excessively heavy accumulation, if necessary. Rinse treated surface thoroughly with high water pressure. Leaves a clean, bright and streak-free finish. With stubborn brake dust and grime, a second application may be required. After wheels are clean and you are washing your vehicle, sponge wheels with a diluted car wash soap (PRO® C-60 Super Car Wash) and rinse thoroughly. This will neutralize any cleaner left over and offer extra corrosion resistance for the wheels and lug nuts. Wipe dry with clean toweling or blow dry with air hose.

SPECIAL NOTES

Always consult wheel manufacturer for care of delicate, aftermarket wheels before using this product as staining may occur.

PACKAGING

GALLON/4 PER CASE
5 GALLON CUBE
55 GALLON DRUM