



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- **Non-Caustic & Non Corrosive**
- **Exterior Cleaner & Degreaser**
- **Won't Harm Sensitive Engine Components or Aluminum**
- **High Foaming Formula Clings to Surface**

- **Breaks down Oil, Grease, Dirt & Road Grime**
- **Ready to Use or Dilute up to 3:1**
- **Nonflammable, Biodegradable**

C-55 NON-CORROSIVE CLEANER & DEGREASER

FEATURES AND BENEFITS

Non-Corrosive Cleaner & Degreaser is a powerful, water base engine cleaner / degreaser formulated without the use of caustic materials. Cleans engine and compartment without harming corrosive-sensitive components. Bulletins are now requesting that NON-CORROSIVE cleaners be used in the engine compartment to reduce chemical etching and component failure when cleaning sensitive areas. Versatile and concentrated (up to 3:1), C-55 can be diluted to use in many different applications. Thick, sudsing formula clings to stubborn residue for maximum cleaning performance. Water emulsified solvents penetrate and dissolve the layers of dirt, oil and grime in minutes. Leaves the engine compartment ready for painting or dressing. Non-Corrosive Cleaner & Degreaser is a safe and effective formulation that eliminates the hazards of caustic, corrosive and solvent base cleaners.

RECOMMENDED FOR

C-55 is designed to quickly penetrate and remove oil and grease deposits, dirt carbon and other road grime from all areas of the engine compartment. Rinses clean with hot or cold water. Can be used in many other automotive cleaning applications. Leaves no oily film or residue.

APPLICATION

Directions: Shake well before using. For your protection, safety glasses and rubber gloves are recommended while using this product. Use a tank sprayer or siphon gun if available.
Engine Degreasing: (RTU or dilute 1:1) - Spray on engine and engine compartment and let stand for 2-3 minutes. Agitate with brush and rinse clean with pressure washer.
HD Cleaning/Degreasing: (dilute 2:1) Door jambs, fuel door, fender wells, etc... Spray on surface and let sit for 30 seconds. Rinse clean with pressure washer.

Wheels & Tires: (dilute 2:1) Clean one wheel at a time. Spray diluted solution onto wheel and tire allow to soak 10-15 seconds. Agitate tire with whitewall brush and use a soft brush or sponge, if necessary, on dirty wheels. Rinse clean with pressure washer.

General Cleaning: (dilute 3:1) Concrete floors, tile, grout and other hard surfaces. Spray on surface and let sit for 1-2 minutes. Agitate with brush and rinse clean.

SPECIAL NOTES

Note: Keep from freezing. Do not apply to a hot surface or let dry on surface. Avoid contact with the painted vehicle finish.

PACKAGING

GALLON / 4 PER CASE
5 GALLON CUBE
55 GALLON DRUM