



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- **Removes Swirls & Fine Scratches after Compounding (3 step)**
- **Enhances Gloss Before Final Finishing (2 step)**
- **Contains No Wax• May be Used as a Finish**
- **Sealer by Hand or Machine (1 Step)**
- **Use with PRO® Eliminator Foam Pads**
- **Durability 30-60 Days**
- **VOC Compliant**

P-21 **SWIRL ELIMINATOR & Polish**

FEATURES AND BENEFITS

P-21 Swirl Eliminator & Polish is an important step in helping detailers attain more perfect finishes. This is a professionally designed product that works well on clear coats as well as other automotive surfaces. Tiny swirls are eliminated quickly with the smooth action of micro abrasives working in harmony with added waxes, oils, cleaners and silicones. P-21 is a single product with results that make it a one step performer. This means that when you have prepared the surface with P-21 you will have a swirl free, glass like finish remaining. Not only does it make the swirls disappear, but it also polishes the vehicle in one operation. It will not harm the delicate basecoat/clearcoat systems on the newer model cars. It can be used by hand to make it even more versatile. P-21 Swirl Eliminator & Polish can solve a lot of problems and should be a staple product in every detailers hands.

RECOMMENDED FOR

- 1) Painted surfaces that have been affected by swirls or compound scratches (3 step).
- 2) Finishes in need of gloss restoration after compounding (2 step).
- 3) Finishes that do not require compounding, but need a high gloss, protective shine (1 step).

APPLICATION

Directions: Shake well before using. Safety glasses and NIOSH dust mask are recommended while using this product. For best results, do not apply in direct sunlight or onto a hot surface.

Hand Use: Apply product to a clean, cotton wax applicator and spread product evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (approx. 3 minutes) and wipe off with a clean, soft, cotton towel. Polish by hand to a high gloss, turning towel while wiping down.

Orbital Use: Apply product to a clean bonnet. Turn on orbital and spread

product evenly over surface. Let dry to a haze (approx. 3 minutes). Remove with a clean, dry bonnet and burnish to a high gloss finish.

High Speed Buffer: Apply product to wax applicator and spread evenly over small area of paint surface before buffing. Use a VF-85-C yellow foam polish pad or RV-85-C charcoal foam finish pad. Buff with adequate pressure @ 1400 - 2300 rpm. As product dries, reduce pressure and burnish to a high gloss. Clean pad often to remove contaminants. Finish with W-41 Yellow Wax, P-35 Satin Creme™ or P-39 Polymer II™ to seal in depth and clarity with long term protection.

SPECIAL NOTES

Do not apply in direct sunlight or onto a hot surface.

PACKAGING

PINT/12 PER CASE
GALLON/4 PER CASE