

The Professional's Choice!  
Since 1935



PRO® and Burford's® are registered trademarks of BAF Industries.

# PRODUCT

## Bulletin



- **Medium Duty Machine Cleaner**
- **Formulated For Clear Coat Finishes**
- **Removes 1200-1500 Wet Sand Scratches, Oxidation & Water Spots**
- **Uses Synthetic Micro-Abrasives**

- **Designed to Buff Fast**
- **Contains No Silicone or Wax**
- **Body Shop Safe**
- **VOC Compliant**

## P-26 CLEAR CUT™ COMPOUND

### FEATURES AND BENEFITS

P-26 Clear Cut™ is a medium duty, machine cleaner formulated for use on urethane and waterbase clear coat (two stage) paint systems. Also works great on acrylic enamel & lacquer paints as well as high solid refinish clears. Removes 1200-1500 wet sand scratches, cobweb scratches and light to medium oxidation. Repairs finishes damaged by acid rain, fallout, chemical etching and other paint irregularities.

Clear Cut™ utilizes the latest developments in abrasive technology with a synthetic micro abrasive particle designed to provide a fast cut, yet is small enough so as not to scratch soft urethane finishes. Clear Cut™ has a thick, creamy consistency that will not run on vertical surfaces. CONTAINS NO WAX OR SILICONE. Water soluble formula cleans up easy out of cracks and crevices by washing or wiping with a damp rag. Leaves a smooth surface ready for polishing or final finishing.

### RECOMMENDED FOR

Body shops, used car dealers, detail shops

and auto auctions. Designed for machine use to remove light to moderate scratches and oxidation, acid rain and fallout damage on factory clears, acrylic enamel and lacquer paint systems. Removes 1200-1500 wet sand scratches, cuts out orange peel, dust nibs and other defects from fresh and fully cured refinish paints. There are no abrasives in P-26 that will scratch the finish, so it is safe and effective for all types of paint systems.

### APPLICATION

**Directions: Shake well before using.** NIOSH approved dust mask and safety glasses are recommended while using this product. For best results, wash car to remove surface grime and dirt, then chamois dry. Start with a new PRO® Buffing Pad. Used pads may contain contaminants which can scratch the surface.

**Aggressive Cutting:** Use with an electric or air buffer (1500-2500 rpm) coupled with a PRO® VC-80-C Wool Buffing Pad. Apply enough product to surface to work a small area (two to four square feet) and spread uniformly before buffing. Start machine at

1200-1700 rpm and buff surface using adequate pressure. As product is used up and begins to dry, increase buffer speed to 2000+ rpm, decrease pressure and burnish to a clean, glossy finish. Leaves a smooth surface ready for polishing or final finishing. Clean pad at regular intervals. Remove any splatter from trim or moldings with a damp cloth.

**For less aggressive cutting and fine scratch removal:** Use PRO® VF-85-C Yellow Foam Buffing Pad at 1200-1700 rpm. Optional: Keep foam pad damp by regularly adding clean water from a spray bottle.

### SPECIAL NOTES

Keep from freezing. Do not apply in direct sunlight or to a hot surface. Follow with a coat of P-34 Progold® Cream Wax to enhance the finish and provide long term protection.

### PACKAGING

Pint/12 per case  
Gallon/4 per case

**BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY U.S.A  
• (800) 437-9893 • (714) 258-8055 • [www.prowax.com](http://www.prowax.com) •