



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!  
Since 1935

# PRODUCT

## Bulletin



- **Contains No Wax or Silicone**
- **Body Shop Safe**
- **Removes 1500-2000 Wet Sand Scratches, Swirl Marks & Minor Imperfections**
- **Non Filling Swirl Remover**
- **Produces a High Gloss finish**
- **Use with Eliminator Foam Pads**
- **Safe on All OEM & Refinish Paints**

## P-28 Vanish™ Machine Glaze

### FEATURES AND BENEFITS

This body shop safe machine glaze removes 1500 - 2000 wet sand scratches and other imperfections on refinish paints. Also repairs cob web scratches, micro scratches and swirl marks after compounding. Its non-silicone, non-wax formula buffs fast and easy with very little dust. Natural oils brighten color and restore depth & clarity. Leaves a durable, high gloss finish. Safe for all OEM and refinish paints.

### RECOMMENDED FOR

Body & paint shops, detail shops, car washes, auto auctions and any application where non-silicone/non wax products are necessary.

### APPLICATION

**Directions: Shake well before using.** Safety glasses and NIOSH dust mask are recommended while using this product. Use an electric or air buffer (1400-2300 rpm) with a PRO® VF-85-C Yellow Foam Polish Pad or RV-85-C Charcoal Foam Finish Pad. Apply a small amount of glaze to painted surface. Center and lay buffing pad directly on top of glaze. Start machine at 1700-2000 rpm and buff surface with medium pressure. Buff evenly over a small (two foot by two foot) area. As glaze begins to dry, reduce pressure and polish surface to a high gloss. Clean pad often to remove contaminants. Wipe off any residue with a clean, PRO® PT-8 Microfiber Towel.

### SPECIAL NOTES

Do not apply in direct sunlight or onto a hot surface.

### PACKAGING

GALLON/4 PER CASE