

The Professional's Choice!
Since 1935



PRO® and Burford's® are registered trademarks of BAF Industries.

PRODUCT

Bulletin



- **One Step Polymer Sealant**
- **Long Lasting (Up to 6 Months)**
- **Safe For All Paints**
- **Durable Architectural Acrylic Resins Seal in a Deep, High Gloss Shine**
- **Protects Against Fading, Oxidation, Acid**

Rain, Fallout, Insects, Bird Droppings & More

- **Contains No Wax**
- **Hand Or DA Application**
- **VOC Compliant**

P-73-Q

PROFECTION™

PAINT SEALANT

FEATURES AND BENEFITS

P-73-Q Profection Paint Sealant is a unique cross-linking formula utilizing the latest polymer resins on the market today.

These new polymer resins penetrate the painted surface forming a bond that seals out the elements. The unique characteristic of Profection is that when the flexible resin cures on the surface it allows the paint to breath. This keeps any moisture from being trapped and clouding the finish.

P-73-Q can be applied over fresh paint. Profection works fast and easy to fill swirl marks, minor scratches and imperfections, while providing the longest lasting high gloss finish available in the industry today.

RECOMMENDED FOR

P-73-Q Profection is designed to clean,

protect and seal new and used automobile finishes. Safe and effective on all automotive finishes.

APPLICATION

SHAKE WELL BEFORE USING. Wash car to remove surface grime and dirt, then chamois dry.

Hand Use: Apply Profection from a dispenser bottle to a clean soft cloth and spread uniformly over entire painted surface. Let dry to a haze. Wipe off with a PT-8 Microfiber Towel and polish by hand to a high gloss finish. Turn cloth at regular intervals.

Orbital/DA Buffer: Apply to orbital bonnet and spread uniformly before buffing. Turn on machine and buff with adequate pressure. Apply to entire painted surface with orbital buffer. Allow sealant to haze, then remove with a clean, dry bonnet and burnish to a high gloss finish.

High Speed Buffer: Use with an electric or air buffer (1500-2500 rpm) coupled with a PRO® RV-85-C Foam Finish Pad. Apply to small area of paint surface and spread uniformly before buffing. Buff with adequate pressure. As product dries, reduce pressure and burnish to a deep luster. Clean pad at regular intervals.

SPECIAL NOTES

Keep from freezing. Do not apply in direct sunlight or to a hot surface. Apply to pre-cleaned surface **ONLY**.

PACKAGING

QUART/12 PER CASE

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY U.S.A
• (800) 437-9893 • (714) 258-8055 • www.prowax.com •