



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT

Bulletin



- **3:1 Concentrate for Desired Gloss**
- **Nonflammable**
- **Sprays Out Clear Restores Original Look to Tires, Bumpers, Moldings, Engines & More**

- **Designed for Rubber, Vinyl & Plastic**
- **Summer Breeze Fragrance**
- **VOC Compliant**

S-71

CLEAR RUBBER DRESSING

Concentrate

FEATURES AND BENEFITS

S-71 CLEAR RUBBER DRESSING is a 3:1 concentrated waterbased dressing that gives new life to all rubber, vinyl and plastic surfaces. Clear Rubber Dressing is PRO®'s economical alternative to the higher priced dressings on the market. One gallon makes four gallons of moderate gloss dressing, when diluted properly with water. For higher gloss, mix 1:1 or 2:1. Repels water upon drying and lasts a long time. Ultraviolet (UV) resistant. Cherry fragrance.

RECOMMENDED FOR

S-71 is the simple inexpensive method for restoring interiors and exteriors. Restores the original "new look" to all rubber surfaces, such as tires, floor mats, trim, moldings and bumpers. Clear Rubber

Dressing is a fantastic engine dressing when diluted 3:1. Use on hoses, wires, cables and all other components in the engine compartment. Leaves engine shiny and it won't collect dust.

APPLICATION

Directions: Shake well before using. For your protection, safety glasses are recommended while using this product. Mix 1 part S-71 with 3 parts water for general use. For high gloss appearance, mix 1:1 or 2:1 with water. For dressing engines, mix 3:1 with water. For best results, pre-clean surface with C-51 Red Devil Degreaser and allow to dry before dressing application.

Tires: With a sprayer, apply product evenly onto a clean, dry tire. Allow 2-3 minutes for runs to dissipate. Dries to a satin gloss finish. Wipe off excess material to avoid unabsorbed product from spinning off

tires onto body panels. For less gloss, apply by wiping on with sponge or terry applicator.

Rubber, Plastic & Vinyl: Wipe on pre-cleaned surface with sponge or terry applicator and let dry.

SPECIAL NOTES

Use only as directed. Not for use on clear plastic (instrument panels), vehicle controls (pedals, grips, steering wheels) or brake discs/drums. Do not drive vehicle immediately after application when tires are wet. Refer to MSDS for additional protective measures.

PACKAGING

GALLON/4 PER CASE