



S-10

**SPRAY ON
LET DRY
WASH OFF**

BUG GUARD™

TEMPORARY PROTECTIVE COATING

- Clear temporary protective coating
- Helps protect vehicle's paint finish against bug kill, bee pollen, road contaminants & rock chips
- Washes off easily with water
- Environmentally safe
- Applies in minutes

**TRY IT!
TODAY!**



THE BENEFITS OF USING BUG GUARD™



CONVENIENCE

You're already here, so why not extend your vehicle's paint protection with a treatment of Bug Guard™? It's the fastest and easiest way to protect your vehicle's finish from paint damaging bug kill.

APPEARANCE

Bug Guard™ dries to a high gloss, transparent coating. The invisible coating enhances and protects the beauty of your finish.

TIME

It takes just a few minutes to apply and 10 minutes to dry. No appointment is necessary.

VALUE

Bug Guard™ offers high tech protection for your paint finish without spending a lot of time and money.

ASK OUR REPRESENTATIVE FOR A BUG GUARD™ TREATMENT WHILE YOU WAIT!

DESCRIPTION



Bug Guard™ is a clear liquid that applies to the front of your vehicle to form a temporary barrier against paint damaging bug kill, bee pollen, road contaminants and rock chips. It dries to an invisible, protective coating. Bugs and contaminants stick to the coating, not your finish. Lovebugs, mayflies, gnats, flies, mosquitoes, dragonflies, bee pollen and other contaminants wash away easily. Safe for painted, plastic, chrome, fiberglass, metal and other non-porous surfaces. Non-flammable, non-toxic and non-corrosive.

RECOMMENDED FOR



Great for all cars, trucks, sport utilities, RV's, vans, motorcycles, rental cars, fleet vehicles, dealer demos, commercial vehicles, truckers, buses, police cars, fire engines, ambulances, farm equipment and more.

HAVE IT APPLIED HERE OR DIY (DO-IT-YOURSELF)



For the do-it-yourselfer, Bug Guard™ is available in a 22 oz. bottle with a sprayer. It can be purchased here or online at prowax.com.



MAINTENANCE



Bug Guard™ is easily removed at your local car wash, detail shop or do it yourself by simply washing the treated area with soap and water. A hard rain will also remove the coating. Reapply after each washing. It can be applied as often as you like and lasts up to a month, if kept dry. However, the coating should not be left on more than 30 days as it is not intended for long term protection.

BG-1

