



Product Bulletin



AWESOME ORANGE™

Product Description:

General purpose cleaner blended from natural citrus extracts and powerful surfactant technology. Removes oil, grease, ink marks, scuff marks, lipstick, crayon marks, smoke film, carbon dust, wax & silicone residue, dirty hand prints, stains and more. Cleans a variety of surfaces with great results. Powerful enough to meet all critical cleaning requirements in most industries, while being safe and environmentally friendly. VOC COMPLIANT.

Product Details:

Biodegradable
VOC Compliant
Water Base
Body Shop Safe
Ready To Use
NPE Free
Phosphate Free
Color: Yellow
Fragrance: Citrus

Packaging:

20 Oz. Can: AAO-500



Features & Benefits:

3 in 1 Product - Degreaser, Wheel & Tire Cleaner and Interior Cleaner
Great For Cleaning Soiled Interiors, Tires, Door Jambs and Engine Compartments
Uses the Cleaning Power of Orange Oil

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hold can in upright position, 8-12 inches (20-30 cm) from surface. Point opening of spray button toward object to be cleaned. Press spray button firmly and spray area liberally until wet with foam.

Soft, Absorbent Surfaces: Spray on surface and let sit several seconds. Blot surface with a clean, damp cloth or agitate with a brush, if necessary. Wipe clean or rinse area as needed.

Hard, Non Porous Surfaces: Chrome, stainless steel, mirrors, tile, porcelain, natural stone: Spray on surface and let sit several seconds. Agitate with a brush, if necessary. Wipe off with a clean, damp cloth or rinse area as needed.

Porous Surfaces: Rubber, plastic, fiberglass, concrete, natural stone, grout: Spray on surface and let sit several seconds. Agitate with a brush, if necessary. Wipe off with a clean, damp cloth or rinse area as needed.

Odor Control: Spray ash trays, trash cans, dumpsters, refuse dumps, etc.. Allow to stand for 1 minute. Wipe off with a clean, damp cloth or rinse area with high pressure water. Repeat if necessary.

Helpful Tips:

Keep from freezing (32 °F/0 °C). For best results, can and material should be at room temperature, 70° F - 90° F (21° - 32°C). Do not apply to hot surface or let dry on surface.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com



INTERNATIONAL
CARWASH
ASSOCIATION®
GROWING. SMARTER. TOGETHER.