



# Product Bulletin



## CALIFORNIA ORANGE™

### Product Description:

California Orange™ is an organic, heavy duty cleaner, degreaser and deodorizer. Its industrial strength formula is blended from natural citrus extracts and meets extra duty cleaning and deodorizing requirements, while still being safe, non-toxic and biodegradable. Removes graffiti, felt pen, indelible ink, scuff marks, tar, gum, asphalt, wax, silicone, oil, grease, tape & adhesive residue, cosmoline, paint overspray, organic fallout, bug residue and other contaminants. BODY SHOP SAFE. VOC COMPLIANT.

### Product Details:

- Biodegradable
- VOC Compliant
- Water Base
- Body Shop Safe
- Ready To Use
- NPE Free
- Phosphate Free
- Color: Yellow
- Fragrance: Citrus

### Packaging:

20 Oz. Can: ACO-660



### Features & Benefits:

- Industrial Strength Cleaner, Degreaser and Deodorizer
- Environmentally Friendly, Biodegradable Formula-Made from Natural Citrus Extracts
- Use for Auto, Industrial, Janitorial & Household Cleaning Applications

### Application: *Shake well before using. Read label before use. See SDS for more information.*

Hold can in upright position, 8-12 inches (20-30 cm) from surface. Point opening of spray button toward object to be cleaned. Press spray button firmly and spray area liberally.

**Soft, Absorbent Surfaces:** Spray on surface and let sit several seconds. Blot surface with a clean, damp cloth or agitate with a brush, if necessary. Wipe clean or rinse area as needed.

**Hard, Non Porous Surfaces:** Spray on surface and allow to stand for 1 minute. Agitate with a brush, if necessary. Wipe off with a clean, damp cloth or rinse area as needed.

**Odor Control:** Spray ash trays, trash cans, dumpsters, refuse dumps, etc..Allow to stand for 1 minute. Wipe off with a clean, damp cloth or rinse area with high pressure water. Repeat if necessary.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). For best results, can and material should be at room temperature, 70°F - 90°F (21° - 32°C). Do not apply to hot surface or let dry on surface. Do not leave on substrate for prolonged period of time, as damage may occur. NOT for use on lexan or clear plastic surfaces. May damage some plastic and painted surfaces. Test on small, inconspicuous area before general use.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

## **BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

