



Product Bulletin



AEROSOL VINYL & CARPET COLOR SPRAY

Product Description:

Burford's® Aerosol Vinyl & Carpet Color Spray revitalizes worn, stained or faded vinyl surfaces, low pile carpets, flexible and rigid plastics and velour quickly and easily. AVC's unique formula bonds with the material to create a tough, permanent, yet flexible, fade resistant coating of brilliant color. Also restores scratched, worn or faded areas on vinyl tops & seats, headrests, door panels, bumpers and other hard plastic surfaces throughout your auto, RV or boat. This quick drying, protective coating is resistant to chipping, peeling and cracking. VOC COMPLIANT.

Product Details:

VOC Compliant
Body Shop Safe
Ready To Use
NPE Free
Phosphate Free
Color: Variety
Fragrance: Unscented

Packaging:

16 Oz. Can: AVC-710 Sandstone
AVC-711 Black
AVC-713 Light Gray
AVC-714 Graphite
AVC-720 Presidio
AVC-726 Warm Gray
AVC-727 Medium Gray



Features & Benefits:

Excellent Adhesion, Flexibility and Coverage
Fanspray Valve Which Provides Wide, Even Spray Pattern
Smooth, Consistent Finish

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hold can in upright position, 8-12 inches (20-30 cm) from surface. Point opening of spray button toward object to be painted. Surface must be clean and dry before painting. Shake can at least one minute before and occasionally during use.

Vinyl & Plastic: Spray thin mist directly on surface with steady, back and forth motion, releasing spray button after each stroke. Allow to air dry.

Carpet: Spray one light coat and immediately brush in all directions using a nylon bristle brush. Apply a second light coat and brush again. After surface has completely dried, brush again to loosen fibers.

Helpful Tips:

Keep from freezing (32 °F/0 °C). For best results, can and material should be at room temperature, 70 °F - 90 °F (21° - 32 °C). Two thin coats are preferable to one heavy coat. If clogging develops, turn spray button 1/4 turn or remove and clean button slot. After use, turn can upside down and spray for two seconds to clear spray button.

Safety Data Sheet:

⚠️WARNING: Cancer & Reproductive Harm - www.p65Warnings.ca.gov. GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

