



# Product Bulletin



## CLAY AWAY™

### Product Description:

An easy to use surface conditioning & preparation bar that removes organic and inorganic contaminants from exterior paint, glass and metal surfaces. CLAY AWAY™ is completely safe, quick and easy to use. This non-toxic cleaning material quickly and easily removes paint overspray, paint finish roughness, fallout, acid rain deposits, rail dust, brake dust and other environmental contaminants from exterior automotive surfaces. Safe for all types of paint finishes. For hand use. Regular grade is recommended for dark colored vehicles. Medium grade is recommended for light colored vehicles. BODY SHOP SAFE. VOC COMPLIANT.

### Product Details:

Ready To Use  
Non-Flammable  
Biodegradable  
VOC Compliant  
Body Shop Safe  
NPE Free  
Phosphate Free  
Color: Gray/Black  
Fragrance: Odorless

### Packaging:

200 g: C-105  
100 g: C-106



### Features & Benefits:

Removes Paint Overspray, Paint Finish Roughness & Environmental Contaminants  
Can Be Safely Used on Paint, Chrome, Aluminum, Plastic and Glass  
Increases Adhesion of Polishes, Waxes, Sealants & Coatings to Painted Surfaces

### Application: *Read label before use. See SDS for more information.*

Wash and rinse vehicle thoroughly using PRO® C-60 Super Car Wash to remove loose dirt and contaminants. Inspect surface to ensure it is free of any loose dirt and debris. Remove CLAY AWAY™ Bar from container. Lubricate surface to be treated by misting with PRO® S-74 Wipeout™ Spray Gloss. Place CLAY AWAY™ Bar in palm of hand and using adequate pressure, begin rubbing CLAY AWAY™ Bar across the lubricated surface in a back and forth (↔) motion until contaminants are removed and surface is smooth and clean. Keep area well lubricated while rubbing. Wipe treated area with a clean, soft towel and inspect surface. Repeat if necessary. Surface is now ready to polish, wax or seal, depending upon the original condition of the paint. After use, always inspect CLAY AWAY™ Bar for dirt or embedded particles that could cause scratching. To preserve CLAY AWAY™ Bar, store in its original container.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Simply stretch and fold CLAY AWAY™ Bar to bring fresh material to the surface. When folding no longer brings up fresh material, discard and use a new piece. Do not use the clay if dropped on the ground. This collected dirt may add surface scratches.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

## **BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

