



Product Bulletin



NON-ACID WHEEL CLEANER

Product Description:

Quickly and easily removes brake dust, metallic particulates, dirt, oil, grease and other surface contaminants from all types of OEM wheels. Designed to eliminate the use of hazardous acid base wheel cleaners. Ready to use or may be diluted 1:1 with water. Simply spray on and rinse off. Non-acid formula safely cleans painted or clear coated aluminum, powder coated, chrome and mag wheels as well as plastic hubcaps and tires. VOC COMPLIANT.

Product Details:

Non-Flammable
VOC Compliant
Water Base
Body Shop Safe
NPE Free
Phosphate Free
Concentrated
pH: 13.5
Color: Green
Fragrance: Floral

Packaging:

Gallon: C-41
5 Gallon Cube: C-41-5
55 Gallon Drum: C-41-55



Features & Benefits:

Safely Cleans & Brightens All Types of OEM Wheels
Removes Brake Dust, Grease, Dirt & Road Grime Without Scrubbing
Spray On, Rinse Off Formula - Leaves No Residue

Application: *Shake well before using. Read label before use. See SDS for more information.*

If wheels are hot, cool wheels with cold water rinse before applying product.

Wheel Cleaning: Dilute up to 1:1 with water for normal wheel cleaning applications.

HD Wheel Cleaning: Use full strength for heavy duty wheel cleaning applications. Clean one wheel at a time. Apply using a pistol sprayer or a tank sprayer. Spray on surface and let sit for 30 seconds. Light agitation with brush may be necessary on excessively dirty wheels. Rinse clean with high pressure water. Leaves a clean and bright finish. Wipe dry with clean towel or blow dry with air hose.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not let dry on surface. Spray on using a drenching effect rather than a fine spray. Do not use on wheel finishes such as non-coated or anodized aluminum. Always consult wheel manufacturer for care of wheels before using this product, as staining may occur. Avoid contact with the painted finish.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

