



Product Bulletin



POWER LIFT™ FALLOUT REMOVER

Product Description:

This ready to use fallout liquid removes organic and inorganic contaminants from automotive paint finishes. Its thick, mild, acid based formula clings to surfaces and offers longer working time for the removal of fallout, acid rain, rail dust, water spots and other contaminants. Sponge onto finish, let sit and rinse off. CONTAINS OXALIC ACID. VOC COMPLIANT.

Product Details:

- Non-Flammable
- Ready To Use
- VOC Compliant
- Water Base
- Body Shop Safe
- Phosphate Free
- pH: 1.5
- Color: Clear
- Fragrance: Floral

Packaging:

Gallon: C-45



Features & Benefits:

- Safely Removes Surface Rust, Water Spots, Iron Particle Fallout and Acid Rain Stains
- Strong Enough To Get The Toughest Fallout To Release
- Safe For All Painted Finishes and Clear Coated Wheels
- Will Not Soften, Fade or Discolor Painted Finish & Trim

Application: *Shake well before using. Read label before use. See SDS for more information.*

If surfaces are hot, cool surface with cold water rinse before applying product. Apply product to a clean sponge or wash mitt and spread evenly over surface to be treated, rubbing lightly to help loosen contaminants. Allow product to sit on surface for 3-5 minutes. Rinse clean with high pressure water to flush away contaminants. Wash vehicle with C-60 Super Car Wash and rinse thoroughly again. This will help to neutralize any residual fallout liquid.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply to a hot surface or let dry on surface. Product is active only while wet.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

