



# Product Bulletin



## XTRACT POWER™

### Product Description:

This powerful stain cleaning concentrate is designed for use in soil extractor machines and pre-spotting on oil, protein and soil based stains on carpet, fabric and upholstery. Its unique combination of surfactants, solvents and wetting agents quickly break down and release stains so they can be easily extracted away. The low foaming formula will not clog jets or pumps and does not require a defoamer in recovery tank. Xtract Power™ is highly concentrated and can be diluted up to 40:1 for economy. Contains a citrus, clean, fresh air fragrance. VOC COMPLIANT.

### Product Details:

Non-Flammable  
Biodegradable  
VOC Compliant  
Water Base  
Body Shop Safe  
NPE Free  
Phosphate Free  
Concentrated  
pH: 12.3  
Color: Amber  
Fragrance: Fresh Air

### Packaging:

Gallon: C-83  
5 Gallon Cube: C-83-5  
55 Gallon Drum: C-83-55



### Features & Benefits:

Extractor Solution & Pre-Spotter  
Powerful 40:1 Concentrate  
Removes Oil, Protein & Soil Based Stains  
Low Foaming Solution Does Not Require Defoamer in Recovery Tank

### Application: *Shake well before using. Read label before use. See SDS for more information.*

Dilute as indicated. May be diluted up to 40:1 with water. Dry brush and thoroughly vacuum area to be cleaned.

**Pre-Spotting:** In a spray bottle, mix a solution of 1 part Xtract Power™ to 3 parts water. Pre-spot stained and heavily soiled areas with solution and allow to dwell 3 minutes. Use extractor to remove. Can be used with hot or cold water extractors.

**Extractor Solution:** Pour 4 ounces of Xtract Power™ per gallon of water (40:1).

**Heavy Duty Solution:** 6 ounces of Xtract Power™ per gallon of water (20:1).

Hot water works best, so allow heater to warm up solution before use. With the pump and vacuum on, depress the trigger. Xtract Power™ solution flows through the head and onto surface, penetrating deep into stained area. Pull wand slowly over stained area where contaminants and cleaning solution are systematically removed, vacuumed back up into recovery tank. Repeat with vacuum only to promote faster drying.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply to hot surface or let dry on surface.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

## BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)



INTERNATIONAL  
CARWASH  
ASSOCIATION®  
GROWING. SMARTER. TOGETHER.