



Product Bulletin



ALL METAL POLISH™

Product Description:


Formulated to clean, polish and protect harder metals like chrome, stainless steel, magnesium and nickel. Also works great on billet & cast aluminum, brass, copper, gold, silver, bronze and other non clear coated metals. Its solvent base, liquid formulation goes on easy and wipes off effortlessly. Quickly removes corrosion, oxidation, stains, rust, tarnish, water spots, tar, grease, bugs and dirt, while restoring the metal's original brilliance. Carnauba wax and natural oils seal in deep shine and offers long term protection. Contains no acid or ammonia. Use on auto & truck trim, stainless tankers, billet aluminum accessories, Harley trim, running boards, diamond plate, ALCOA, Centerline & other custom wheels, marine hardware, engine accessories, metal cookware, jewelry and more. For hand or machine use. VOC COMPLIANT.

Product Details:

VOC Compliant
NPE Free
Phosphate Free
pH: 8.5
Color: Light Blue
Fragrance: Odorless

Packaging:

Pint: C-90-P



Features & Benefits:

Cleans, Polishes & Protects All Types of Metal
Removes Oxidation, Rust, Corrosion, Stains, Tarnish, Water Spots & More
Seals in Deep Shine with Long Lasting Carnauba Wax

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over surface, rubbing well in a back and forth motion, with the grain of the metal, until a black residue appears. On chrome, clear coated and non metal surfaces, no residue will appear. Let dry to a haze (about 1 min.) and wipe off with a clean, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down. Reapply as needed.

D/A Polisher: Use a PRO® YU-7-C D/A Yellow Light Polish Pad. Apply product to pad. Set dual action polisher to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a PRO® VC-80-C Wool Buffing Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of metal surface before buffing. Buff product with adequate pressure at 1200-2000 rpm. As product dries, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants.

Helpful Tips:

Keep from freezing (32 °F/0 °C). NIOSH approved dust mask and safety glasses are recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. Not for use on automotive paint finishes.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com



INTERNATIONAL
CARWASH
ASSOCIATION®
GROWING. SMARTER. TOGETHER.