



# Product Bulletin



## GADNIUM METAL POLISH™

### Product Description:


A unique paste metal polish that cleans, polishes and protects all types of metal surfaces. Quickly removes corrosion, oxidation, rust, tarnish, water spots, lime deposits, rubber black streaks, heat discoloration, dirt, graffiti and more while restoring the metal's original brilliance. Its easy to use "wipe on, wipe off" formula works great on chrome, stainless steel, magnesium, nickel, billet & cast aluminum, brass, copper, gold, silver, bronze, pewter, tin, titanium, platinum, silver plate, sterling and other non clear coated metals. Also works great on other non-metal surfaces such as acrylic, poly carbonate, glass, fiberglass, crystal, Corian®, Formica, marble, granite, porcelain and painted surfaces. Carnauba wax and natural oils seal in deep shine and offers long term protection. Contains no acid or ammonia. For hand or machine use. VOC COMPLIANT.

### Product Details:

- VOC Compliant
- NPE Free
- Phosphate Free
- pH: 8.3
- Color: Light Blue
- Fragrance: Odorless

### Packaging:

Quart: C-92-P



### Features & Benefits:

- Cleans, Polishes & Protects All Types of Metal
- Removes Oxidation, Rust, Corrosion, Stains, Tarnish, Water Spots & More
- Leaves a Brilliant Waterproof Surface with Long Lasting Carnauba Wax

### Application: *Shake well before using. Read label before use. See SDS for more information.*

**Hand Use:** Apply product to a clean microfiber wax applicator and spread evenly over surface, rubbing well in a back and forth motion, with the grain of the metal, until a black residue appears. On chrome, clear coated and non metal surfaces, no residue will appear. Let dry to a haze (about 1 min.) and wipe off with a clean, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down. Reapply as needed.

**D/A Polisher:** Use a PRO® YU-7-C D/A Yellow Light Polish Pad. Apply product to pad. Set dual action polisher to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

**High Speed Buffer:** Use a PRO® VC-80-C Wool Buffing Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of metal surface before buffing. Buff product with adequate pressure at 1200-2000 rpm. As product dries, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). NIOSH approved dust mask and safety glasses are recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. Not for use on automotive paint finishes.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).



# BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

