



# Product Bulletin



## DOUBLE CUT™

### Product Description:

Double Cut™ is an aggressive low swirl, correcting compound designed to remove heavy surface imperfections. Fast removal of 1000-1200 grit sand scratches, severe swirls, holograms and heavy oxidation. May be applied by D/A or rotary variable speed polisher. Works well with wool or foam cutting pads. Leaves a clean, glossy surface ready for polishing. For machine use. CONTAINS NO WAX OR SILICONE. BODY SHOP SAFE. VOC COMPLIANT.

### Product Details:

VOC Compliant  
Body Shop Safe  
NPE Free  
Phosphate Free  
pH: 9.3  
Color: White  
Fragrance: Floral

### Packaging:

Quart: P-16-Q



### Features & Benefits:

Removes Heavy Surface Imperfections, Holograms, & 1000-1200 Grit Wet Sand Scratches  
Designed for DA Compound Correction  
Uses High Purity Aluminum Oxide Abrasive System  
Low Dust, Silica-Free Formula  
Great for Marine Gel Coat & Fiberglass Surfaces  
Body Shop Safe – Contains No Wax or Silicone

**Application:** *Shake well before using. Read label before use. See SDS for more information.*

**D/A Polisher:** Use a PRO® BU-6 Blue All in One Polish Pad. For more aggressive action, use a PRO® MU-6 Maroon Compound Pad. Apply product to pad. Set dual action polisher to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

**High Speed Buffer:** Use a PRO® VC-80-C Wool Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-1800 rpm. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants. Follow with a P-21 Swirl Eliminator™ and a PRO® RV-85-C Charcoal Foam Polish Pad.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Safety glasses and NIOSH approved dust mask are recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

## **BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

