



# Product Bulletin



## ULTIMATE CUTTER™

### Product Description:

Versatile machine compound is formulated for use on aftermarket high solid clearcoat finishes, standard OEM clears and conventional paints. Its unique micro-abrasive system allows aggressive cutting for hard, high solid clearcoats and commercial paints, yet is gentle enough for cutting and polishing softer coatings like OEM clearcoats, enamels and lacquers. Removes 1000-1200 grit wet sand scratches, oxidation, orange peel and other minor defects. Buffs quickly, leaving a clean, smooth surface ready for polishing. Water soluble formula cleans up easy out of cracks and crevices. For machine use only. CONTAINS NO WAX OR SILICONE. BODY SHOP SAFE. PHOSPHATE-FREE. NPE-FREE. VOC COMPLIANT.

### Product Details:

- VOC Compliant
- Body Shop Safe
- NPE Free
- Phosphate Free
- pH: 9.1
- Color: White
- Fragrance: Floral

### Packaging:

- Quart: P-27-Q
- Gallon: P-27



### Features & Benefits:

- Aggressive, Dual Micro Particle Synthetic Abrasive System
- Removes 1000-1200 Grit Wet Sand Scratches
- Leaves a Smooth Surface Ready for Polishing
- Body Shop Safe - Contains No Wax or Silicone

**Application:** *Shake well before using. Read label before use. See SDS for more information.*

**D/A Polisher:** Use a PRO® MU-6 Maroon Medium Cut Pad. Apply product to pad. Set D/A polisher speed to 4-6. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants. Follow with a PRO® BU-6 Blue Polish Pad and P-21 Swirl Eliminator™.

**High Speed Buffer:** Use a PRO® VC-80-C Wool Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-1800 rpm. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants. Follow with a PRO® RV-85-C Charcoal Foam Polish Pad and P-21 Swirl Eliminator™.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). NIOSH approved dust mask is recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

### Safety Data Sheet:

GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).

# BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • [www.prowax.com](http://www.prowax.com)

