



# Product Bulletin



## BLACK BEAUTY™

### Product Description:

One-step color brightener and sealer, specially formulated for black and other dark color paints. Quickly and effectively removes fine swirl marks and cobweb scratches, while leaving a darker, more reflective finish. Contains amino functional silicones and Carnauba Wax for long term, high gloss protection. Safe for all types of paint finishes. For hand or machine use. VOC COMPLIANT.

### Product Details:

VOC Compliant  
NPE Free  
Phosphate Free  
pH: 8.4  
Color: Black  
Fragrance: Floral

### Packaging:

Pint: P-29-P  
Gallon: P-29



### Features & Benefits:

Specifically Formulated for Black & Other Dark Color Paint Finishes  
Micro Abrasives Remove Fine Swirl Marks, Cobweb Scratches & Paint Finish Roughness  
Produces a Darker, More Reflective Paint Finish  
Blend of Carnauba Wax & Polymers Yield a Deep, Dark Protective Shine

**Application:** *Shake well before using. Read label before use. See SDS for more information.*

**Hand Use:** Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 2 min.) and wipe off with a clean, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

**D/A Polisher:** Use a PRO® YU-7-C Yellow Polish Pad. For more aggressive action, use a PRO® BU-7-C Blue Compound Pad. Apply product to pad. Set D/A polisher speed to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

**High Speed Buffer:** Use a RV-85-C Charcoal Foam Polish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1500-2300 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants. For added protection, finish with PRO® P-36 Cherry Finishing Wax™, P-63-Q Poly Gard™ or P-82 Carnauba Creme Wax™.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

### Safety Data Sheet:

**⚠️WARNING:** Reproductive Harm - [www.p65Warnings.ca.gov](http://www.p65Warnings.ca.gov). GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).



## BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

