



# Product Bulletin



## AUTO AUCTION PREP™

### Product Description:

Thick polish/wax combination is a fast and easy one-step polish designed especially for the demands of high volume auto auctions. Cleans, polishes and waxes in one easy operation. Removes light oxidation, fine scratches and swirl marks, while natural oils restore gloss and enhance depth. Imported waxes offer lasting, high gloss protection. Safe for all types of paint finishes. For hand or machine use. VOC COMPLIANT.

### Product Details:

VOC Compliant  
NPE Free  
Phosphate Free  
pH: 8.5  
Color: Green  
Fragrance: Floral


### Packaging:

Gallon: P-47



### Features & Benefits:

Cleans, Polishes & Waxes in One-Step  
Easy To Use, Fast Buffing Formula  
Removes Swirl Marks & Light Scratches  
Produces a Lasting, High Gloss Shine



**Application:** *Shake well before using. Read label before use. See SDS for more information.*

**Hand Use:** Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 1 min.) and wipe off with a clean microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

**D/A Polisher:** Use a PRO® YU-6 Yellow Polish/Finish Pad. For more aggressive action, use a PRO® BW-6 Black/White Microfiber Polish Pad. Apply product to pad. Set D/A polisher speed to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

**High Speed Buffer:** Use a RV-85-C Charcoal Foam Polish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure @ 1500-2300 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants. For added protection, finish with P-36 Cherry Finishing Wax™, P-63-Q Poly Gard™ or P-82 Carnauba Creme Wax™.

### Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

### Safety Data Sheet:

⚠️ **WARNING:** Reproductive Harm - [www.p65Warnings.ca.gov](http://www.p65Warnings.ca.gov). GHS Compliant. SDS can be found online at [www.prowax.com](http://www.prowax.com).



## **BAF Industries**

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY  
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • [www.prowax.com](http://www.prowax.com)

