



Product Bulletin



POLY GARD™ PAINT SEALANT

Product Description:

High quality paint sealant produces a long lasting, high gloss shine on all types of automotive paint finishes. Mild cleaner removes light scratches, oxidation and contaminants, while glossing agents restore shine and clarity. Two penetrating, amino-functional polymer resins cure to form a continuous, durable film that will out last any wax product. Resists UV rays, salt air, snow, rain, insects, road film, harsh detergents and environmental contaminants that can fade or discolor automotive finishes prematurely. Reduces friction buildup so contaminants will not adhere to the surface. Offers up to 6 months of lasting beauty and protection. Apply by hand or machine. CONTAINS NO WAX. VOC COMPLIANT.

Product Details:

VOC Compliant
NPE Free
Phosphate Free
pH: 9.0
Color: Light Blue
Fragrance: Cherry

Packaging:

Pint: P-63-P
Quart: P-63-Q



Features & Benefits:

Durability Far Superior To Wax
Durable Polymer Resins Enhance Color & Seal In A Deep Gloss Shine
Outstanding Detergent Resistance & Water Repellency That Lasts Up To Six Months
Protects Against Salt Water, UV Rays, Environmental Pollutants, Insects, Bird Droppings & More

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (2 min.) and wipe off with a clean microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

D/A Polisher: Use a PRO® YU-6 Yellow Polish/Finish Pad. Apply product to pad. Set D/A polisher speed to 3-4. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a PRO® WV-85-C White Foam Finish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-2000 rpm. As product disappears, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. For best results, pre-clean finish to remove contaminants and to condition paint. Polish one section at a time.

Safety Data Sheet:

⚠️WARNING: Reproductive Harm - www.p65Warnings.ca.gov. GHS Compliant. SDS can be found online at www.prowax.com

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com



INTERNATIONAL
CARWASH
ASSOCIATION®
GROWING. SMARTER. TOGETHER.