



Product Bulletin



POLY GARD™ PAINT SEALANT

Product Description:

This high quality paint sealant produces a long lasting, high gloss shine on all types of automotive paint finishes. Mild cleaner removes light scratches, oxidation and contaminants, while glossing agents restore shine and clarity. Two penetrating, amino-functional polymer resins cure to form a continuous, durable film that will out last any wax product. Poly Gard™ resists UV rays, salt air, snow, rain, insects, road film, harsh detergents and environmental contaminants that can fade or discolor automotive finishes prematurely. Poly Gard™ Paint Sealant reduces friction buildup so contaminants will not adhere to the surface. Poly Gard™ offers up to 6 months of lasting beauty and protection. Apply by hand or machine. CONTAINS NO WAX. VOC COMPLIANT.

Product Details:

VOC Compliant
NPE Free
Phosphate Free
pH: 9.0
Color: Light Blue
Fragrance: Cherry

Packaging:

Pint: P-63-P
Quart: P-63-Q



Features & Benefits:

Durability That Is Far Superior To Wax
Durable Polymer Resins Enhance Color & Seal In A Deep Gloss Shine
Outstanding Detergent Resistance & Water Repellency That Lasts Up To Six Months
Protects Against Salt Water, UV Rays, Environmental Pollutants, Insects, Bird Droppings & More

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (2 min.) and wipe off with a clean microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

D/A Polisher: Use a PRO® WU-7-C White Finish Pad. Apply product to pad. Set D/A polisher speed to 3-4. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a PRO® WV-85-C White Foam Finish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-2000 rpm. As product disappears, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. For best results, pre-clean finish to remove contaminants and to condition paint. Polish one section at a time.

Safety Data Sheet:

⚠️WARNING: Reproductive Harm - www.p65Warnings.ca.gov. GHS Compliant. SDS can be found online at www.prowax.com



BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

