

# **Product Bulletin**



## CARNAUBA CREME WAX<sup>™</sup>

#### Product Description:

Premium final finish creme wax is made with #1 Grade Brazilian Carnauba and natural oils that produce an ultra rich, deep gloss shine. Nano particle infused resins bond to surface to improve durability and long lasting protection. Contains banana oil to enrich dry surfaces and offer a pleasing fragrance. The fast working formula offers low dusting qualities with easy removal and clean up. Safe for all types of paint finishes. For hand or machine use. VOC COMPLIANT.

#### Product Details:

VOC Compliant NPE Free Phosphate Free pH: 9.6 Color: Yellow Fragrance: Banana



### Features & Benefits:

Premium Finish Wax Made With #1 Grade Brazilian Carnauba Nano Particle Infused Resins Bond to Surface to Improve Durability Produces an Ultra Rich, Deep Gloss Shine With Long Lasting Protection Banana Oil Enriches Dry Surfaces Low Dust, High Durability Formula

#### **Application:** Shake well before using. Read label before use. See SDS for more information.

**Hand Use:** Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 1 min.) and wipe off with a clean microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

**D/A Polisher:** Use a PRO<sup>®</sup> YU-6 Yellow Polish/Finish Pad. Apply product to pad. Set D/A polisher speed to 3-4. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants.

**High Speed Buffer:** Use a PRO<sup>®</sup> WV-85-C White Foam Finish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-2000 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants.

#### <u>Helpful Tips:</u>

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. For best results, preclean finish to remove contaminants and to condition paint. Polish one section at a time.

#### Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.



1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY (800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

