



Product Bulletin



SYNERGY CERAMIC PAINT COATING

Product Description:

Synergy Ceramic Coating represents a revolutionary advance in paint protection. Synergy is a semi-permanent, super hydrophobic nano ceramic coating specifically designed for painted finishes. This high tech coating creates an extremely hard, slick, clear barrier of protection on painted finishes. Synergy chemically bonds with the factory paint by penetrating the vehicle's clear coat finish to form a second layer and thicker coating for added protection. VOC COMPLIANT.

Product Details:

VOC Compliant
Body Shop Safe
Ready To Use
NPE Free
Phosphate Free
Color: Clear
Fragrance: Solvent

Packaging:

50ml (1.7 oz. Bottle): S-1



Features & Benefits:

9H Hardness
Super Hydrophobic Effect
Weather & Chemical Resistant
Heat & UV Resistant
High Gloss Finish
Durability: Protects up to 24 months

Application: *Shake well before using. Read label before use. See SDS for more information.*

Wash vehicle using PRO® C-60 Super Car Wash. Decontaminate the paint using PRO® C-44-Q Reactive™ or PRO® C-105 Clay Away™. Compound or polish if necessary to remove any imperfections. Wipe down the surface to be coated with PRO® C-61 PRO®-Sol™. Wrap foam applicator block with microsuede applicator cloth. Pour Synergy Ceramic Paint Coating slowly onto applicator cloth until saturated. Apply a thin coating over a small area using a crisscross pattern to maintain even coverage. Apply more product as needed to keep a wet, even application. Allow product to flash (30 seconds) then gently wipe surface with a clean, dry microfiber towel. Allow coating to bond 1 minute. Using a clean, dry microfiber towel, apply medium pressure, wipe the area clean and dry of any residue. Gently buff to a high shine. Repeat steps until all exterior painted surfaces are coated.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Recommended application temperatures 40° - 90° F. Do not apply in direct sunlight or to hot surface. Apply in dust free, shaded area. Additional coats may be applied for increased protection, shine, hardness and durability. Avoid washing vehicle for 5 days after application. Keep surface dry for 8-12 hours after application. Allow to cure for 24 hours before exposure to water or the environment. Apply Synergy Ceramic Detail Spray after every wash or as needed to restore hydrophobicity and gloss.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

