1 Identification of the substance and manufacturer

Trade name:
Product code:

Recommended use: Uses advised against: Manufacturer/Supplier:

LIGHT GRAY

AVC-713 Paint and coatings application. Any that differs from the recommended use. BAF Industries 8010 Dixie Highway Florence, KY 41042 USA Phone: 859-372-5900 msds_info@prowax.com Emergency Information: ChemTrec 800-424-9300 If outside USA, 703-527-3887

2 Hazard(s) identification

2 Hazard(s) Identification		
Classification of the substance or mixture		
Flam. Aerosol 1 H222 Extremely flammable aerosol.		
Press. Gas H280 Contains gas	s under pressure; may explode if heated.	
Skin Irrit. 2 H315 Causes skin	irritation.	
Eye Irrit. 2A H319 Causes serio	bus eye irritation.	
Repr. 1B H360 May damage	e fertility or the unborn child.	
	rowsiness or dizziness.	
STOT RE 2 H373 May cause d	amage to organs through prolonged or repeated exposure.	
Additional information:		
GHS Hazard pictograms	GHS02 GHS04 GHS07 GHS08	
Signal word	Danger	
Signal word Hazard statements	Extremely flammable aerosol.	
	Contains gas under pressure; may explode if heated.	
	Causes skin irritation.	
	Causes serious eye irritation.	
	May damage fertility or the unborn child. May cause drowsiness or dizziness.	
	May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	Obtain special instructions before use.	
-	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	Do not spray on an open flame or other ignition source.	
	Pressurized container: Do not pierce or burn, even after use.	
	Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.	
	Use only outdoors or in a well-ventilated area.	
	Wear protective gloves/protective clothing/eye protection/face protection.	
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
	Call a poison center/doctor if you feel unwell.	
	Specific treatment (see on this label).	
	Take off contaminated clothing and wash it before reuse.	
	If eye irritation persists: Get medical advice/attention.	
	Store in a well-ventilated place. Store locked up.	
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
	Dispose of contents/container in accordance with local/regional/national/international regulations.	

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous components:		
67-64-1 Acetone		25-50%
108-88-3 Toluene		≥20-≤25%
74-98-6 propane		15-25%
106-97-8 n-butane		5-10%
2807-30-9 Glycol Ether EP		1-5%
108-65-6 PM acetate		1-5%

4 First-aid measures After inhalation:

Supply fresh air; consult doctor in case of complaints.

(Contd. on page 2)

Revised On 10/14/2021

After skin contact: Immediately wash with water and scap and inse thoroughly. After sevol contaminated cohting. Wash washed area with scap and water. After sevol month and the chink. Period and the chink peetry of the principal and water. Most important symptoms and effects: Discinces Most important symptoms and effects: Discinces Prof.philing measures Extinues Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Con form sciposity gas-air mixtures. Prof.philing measures Co2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Con form sciposity gas-air mixtures. Prof.ort sciposition and emergery. Prof.ort sciposition gas and material for containmand cohtwoice against the effects of furnes/dustaerosol. Methods and material for containmand cohtwoice against the directs of furnes/dustaerosol. Ensure adequate ventilation. Dispose containmand cohtwoice against the sciposition gas away. Keep away from sources of head and mixel as waste according to section 13. Handling and storage Use only in well ventilated areas. Keep away from sources of head and mixel and fired sunlight. Do not warehouse in subfreezing conditions for service and part in the sciposition of the sciposition of the sciposition of the sciposition of thead areas. </th <th>ing date 10/14/202</th> <th>.1</th> <th>Revised On 10/14/20</th>	ing date 10/14/202	.1	Revised On 10/14/20
After skin contact: Immediately wash with water and scap and inse thoroughly. After sevol contaminated cohting. Wash washed area with scap and water. After sevol month and the chink. Period and the chink peetry of the principal and water. Most important symptoms and effects: Discinces Most important symptoms and effects: Discinces Prof.philing measures Extinues Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Con form sciposity gas-air mixtures. Prof.philing measures Co2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Con form sciposity gas-air mixtures. Prof.ort sciposition and emergery. Prof.ort sciposition gas and material for containmand cohtwoice against the effects of furnes/dustaerosol. Methods and material for containmand cohtwoice against the directs of furnes/dustaerosol. Ensure adequate ventilation. Dispose containmand cohtwoice against the sciposition gas away. Keep away from sources of head and mixel as waste according to section 13. Handling and storage Use only in well ventilated areas. Keep away from sources of head and mixel and fired sunlight. Do not warehouse in subfreezing conditions for service and part in the sciposition of the sciposition of the sciposition of the sciposition of thead areas. </th <th>de name: LIGI</th> <th>HT GRAY</th> <th></th>	de name: LIGI	HT GRAY	
After eve contact: Runse opened eve for even imminutes under numning water. Runse opened even for even imminutes under numning water. Runse opened even for even imminutes under numning water. Runse numning w	After ekin co	ntaati	(Contd. of page
After eye contact: Rines opened eye for several minutes under running water. If symptoms persist, consult a doctor Rine and minicipative of value. Mars simportant symptoms and effects: Disziness Indication of any immediate medical attention needed: Disziness No further relevant information available. Disziness Fire-fighting measures CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Protective equipment for three protective equipment. Keep unprotected persons away. Protective equipment and end end position of three spray. Wathods and material for containmated material as waste according to section 13. Dispose containmated material as waste according to section 13. Handling and storage Proceutions for safe handing Storage opping them sources of heat and direct sunlight. Do not warehouse in subfreezing condition. Storage requirements. Keep avaip from sources of heat and direct sunlight. Do not warehouse in subfreezing condition. Storage requirements. Keep avaip from sources of heat and direct sunlight. Do not warehouse in subfreezing condition. Storage requirements. Keep avaip from sources of heat and direct sunlight. Co not warehouse in subfreezing condition. Toring back personal protection Components with limit values 2400 mg/m². 1000 ppm	Aller SKIN CO	maCl.	Remove contaminated clothing. Wash exposed area with soap and water
Most important symptoms and efficities Rinse mouth with water. Do not induce vomiting. West important symptoms and efficities Dizziness File-fighting measures No further relevant information available. Extinguishing agents: Co2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures. Protective equipment for infefighters: A respiratory protective device may be necessary. Accidental release measures Personal precautions, protective equipment and emergency Wear protective equipment. Keep unprotected persons away, procedures: Wear protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up. Exposure controls/personal protection Components with limit value: 2400 mg/m³, 1000 ppm Long-term value: 260 mg/m³, 250 ppm TV (USA) Long-term value: 260 mg/m³, 150 ppm TV (USA) Cong-term value: 260 mg/m³, 150 ppm TO mp pack per 4-tr shift TO mp agent pack in thotogenem TV (USA) Long-term value: 180 mg/m³, 150 ppm TV (USA) Long	After eye con	itact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Most important symptoms and firsts: Indication of any immediate modula Disziness No further relevant information available. Fire-fighting measures Extinguishing agents: C22, extinguishing powder or water spray. Fight larger fires with water spray. Gan form explosive gasar initiatives. Can form explosive gasar initiatives. Can form explosive gasar initiatives. Can form explosive gasar initiatives. A respiratory protective device may be necessary. Accidental release measures Personal processitions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of turnes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of turnes/dust/aerosol. Methods and material for containment and cleaning up: Encure adequipte vanillation. Dispose contaminated material as waste according to section 13. Handling and storage Proceations for safe handling Storage requirements: Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acetone PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose components with limit values that require monitoring at the workplace: 67-64-1 Acetone PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose promate: 1800 mg/m ³ , 100 ppm TU (USA) Dispose promate: 1800 mg/m ³ , 100 ppm TU (USA) Dispose prome PEL (USA) Long-term value: 200 mg/m ³ , 200 ppm TU (USA) Dispose promate: 200 mg/m ³ , 100 ppm TU (USA) Dispose promate: 200 mg/m ³ , 10	After swallov	ving:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting
Indication of any immediate medical indication of any immediate medical indication of any immediate medical information available. Fire-fighting measures Protective equipment for frefighters: A capital argent mixtures. Can form explosive gas-atr mixtures. Can form explosive gas-atr mixtures. Accidental release measures Personal precautions, protective quipment and emergency Wear protective device may be necessary. Accidental releases measures Personal precautions, protective quipment and emergency Wear protective device may be necessary. Accidental information protective device may be necessary. Accidental information of the second protective device against the effects of times/dust/aerosol. Methods and material for containment and cleaning up: Dispose contamineted material as waste according to section 13. Handling and storage Procautions for safe handling Storage requirements: Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 76-641 Acctone FEL (USA) Long-term value: 2000 mgm ² , 2000 ppm LTV (USA) Long-term value: 2000 mgm ² , 2000 ppm TUV (USA) Long-term value: 2000 mgm ² , 2000 ppm TUV (USA) Conjecterm value: 2000 mgm ² , 2000 ppm TUV (USA) Long-term value: 2		ant symptoms and	
attention needed: No further relevant information available. Fire-fighting measures Exitinguishing geoms: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special heards: Can form explosive gas-air mixtures. Protective equipment for explosive gas-air mixtures. Protective equipment and emergency protective equipment. Keep unprotected persons away, procedures: Wear protective equipment. Keep unprotects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions for the code up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acction PEL (USA) Long-term value: 200 mg/m² - 250 ppm Long-term value: 504 mg/m² - 550 ppm Edil mint value: 504 smg/m² - 550 ppm PEL (USA) Long-term value: 200 ppm Cangeterm value: 200 ppm Edil mint value: 300 smg/m² - 550 ppm PEL (USA) Long-term value: 200 ppm Cangeterm value: 200 ppm Edil mint value: 500 ppm		any immediate medica	
Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Coal form explosive gas-air mixtures. Protective equipment for firefighters: A respiratory protective device may be necessary. Accidental release measures Personal precautions, protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/arosol. Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Precautions for safe handling Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Storage requirements: Storage locked up. Exposure controls/personal protection Con form sources of heat and direct sunlight. Do not warehouse in subfreezing condition Clush Long-term value: 2400 mg/m², 1000 ppm Et (USA) Long-term value: 250 ng/m², 250 ppm UV (USA) Long-term value: 300 mg/m², 1000 ppm Et (USA) Long-term value: 300 mg/m², 150 ppm LUSA Long-term value: 300 mg/m², 150 ppm Et (USA) Long-term value: 300 mg/m², 150 ppm LUSA Long-term value: 300 mg/m², 150 ppm Et (USA) Long-term value: 300 mg/m², 150 ppm	attention nee	ded:	No further relevant information available.
Extinguishing agents: Special hazards: Protoctive equipment for infighters: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures. Protoctive equipment and emergency procedures: Wear protoctive device may be necessary. Accidential release measures Personal precautions, protective equipment and emergency procedures: Containment and cleaning up: Ensure adequate ventilation. Dispose containinated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Storage requirements: Case only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acctore PEL (USA) Long-term value: 2400 mg/m², 1000 ppm Lag entry value: 250 ppm Lag entry value: 2370 mg/m², 100 ppm Lag entry value: 2370 mg/m², 100 ppm Lag entry value: 2370 mg/m², 100 p	Fire-fighting	g measures	
Protective equipment for firefighters: A respiratory protective device may be necessary. Accidential release measures Personal procesurions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away, Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Storage requirements: Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acctone PEL (USA) Long-term value: 2400 mg/m ² , 1000 ppm Long-term value: 2400 mg/m ² , 250 ppm Long-term value: 300 spm pm Long-term value: 300 spm pm Longoterm value: 300 spm pm Long-term value: 300			CO2, extinguishing powder or water spray. Fight larger fires with water spray.
firefighters: A respiratory protective device may be necessary. Accidental release measures Personal precatitions, protective device equipment. Keep unprotected persons away. Veer protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Use only in well ventilated areas. Ensure adequate ventilation. Storage requirements: Use only in well ventilated areas. Storage requirements: Use only in well ventilated areas. F24-1 Acctone Components with limit values that require monitoring at the workplace: 67-64-1 Acctone PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm Display mg/m³, 250 ppm TLV (USA) Long-term value: 300 mg/m³, 100 ppm EB Bell Nort-term value: 300 mg/m³, 100 ppm EB VI (USA) Long-term value: 300 mg/m³, 100 ppm Display material as waste according to section TLV (USA) Long-term value: 300 mg/m³, 100 ppm EB REL (USA) Long-term value: 300 mg/m³, 1000 ppm RE <t< td=""><td>Special haza</td><td>rds: juipment for</td><td>Can form explosive gas-air mixtures.</td></t<>	Special haza	rds: juipment for	Can form explosive gas-air mixtures.
Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acctone PEL (USA) Long-term value: 2400 mg/m², 1000 ppm (mg/m², 250 ppm (mg/m², 250 ppm) (Data) PEL (USA) Long-term value: 594 mg/m², 250 ppm (Data) Storage requirements: 504 mg/m², 250 ppm (Data) PEL (USA) Long-term value: 500 mg/m², 250 ppm (Data) Storage requirements: 504 mg/m², 250 ppm (Data) PEL (USA) Long-term value: 500 mg/m², 150 ppm (Data) Caling limit value: 306, 500° ppm (To-mm peak per 8-hr shift (Data) PEL (USA) Long-term value: 200 ppm (EL) (NCA) Long-term value: 375 mg/m², 100 ppm (Data) PEL (USA) Long-term value: 20 ppm (EL) (NCA) Long-term value: 1800 mg/m², 1000 ppm (Data) PEL (USA) Long-term value: 1800 mg/m², 1000 ppm (EL) (NCA) Long-term value: 20 ppm (EL) (NCA) Dag-term value: 1800 mg/m², 1000 ppm (EL) (NCA)	firefighters:		A respiratory protective device may be necessary.
Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64 - Acctone PEL (USA) Long-term value: 2400 mg/m², 1000 ppm (m², 250 ppm) BEI 108-83 Toluene PEL (USA) Long-term value: 594 mg/m², 250 ppm (m², 250 ppm) BEI Short-term value: 304 mg/m², 100 ppm (m², 250 ppm) (m², 250 ppm) (m	Accidental I	release measures	
procedures: Wear protective equipment. Keep unprotected persons away. Wethods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: C74-41 Acetone Comptonents with limit values that require monitoring at the workplace: PEL (USA) Long-term value: 500 mg/m³, 1000 ppm TLV (USA) Short-term value: 500 mg/m³, 500 ppm BEI Cong-term value: 500 mg/m³, 500 ppm T0-min peak per 8-th shift REL (USA) Long-term value: 500 mg/m³, 100 ppm BEI Cong-term value: 500 mg/m³, 100 ppm T0-min peak per 8-th shift REL (USA) Long-term value: 500 mg/m³, 100 ppm BEI Cong-term value: 500 mg/m³, 100 ppm T0-min peak per 8-th shift REL (USA) Long-term value: 500 mg/m³, 100 ppm T1/V (USA) Long-term value: 300 mg/m³, 100 ppm T0-min peak per 8-th shift REL (USA) Long-term value: 1800 mg/m³, 1000 ppm T1/V (USA) Long-term value: 300 mg/m³, 1000 ppm T0/T (USA) Long-term value: 1900 mg/m³, 1000 ppm T1/V (USA) Long-term value: 1900 mg/m³, 1000 ppm T1/V (USA) </td <td>Personal pre</td> <td>cautions, protective</td> <td></td>	Personal pre	cautions, protective	
Use respiratory protective device against the effects of fumes/dust/aerosol. We respiratory protective device against the effects of fumes/dust/aerosol. We respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation. Dispose contraminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Fee away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: Fee (USA) Long-term value: 2400 mg/m², 1000 ppm REL (USA) Long-term value: 2400 mg/m², 1000 ppm BEI USA: Stort-term value: 200 ppm Celling limit values 305 mg/m², 250 ppm DEL (USA) Long-term value: 200 ppm Celling limit value: 300 mg/m², 150 ppm Long-term value: 200 ppm Celling limit value: 305 mg/m², 150 ppm Long-term value: 200 ppm Celling limit value: 305 mg/m², 150 ppm Long-term value: 200 ppm BEI USA: Long-term value: 200 ppm Celling limit value: 300 mg/m², 150 ppm Long-term value: 200 ppm Celling limit value: 300 mg/m², 150 ppm Long-term value: 200 ppm Celling limit value: 300 mg/m², 150 ppm Long-term value: 300 mg/m², 1000 ppm LV (USA) Long-term value: 1800 mg/m², 1000 ppm LV (USA) Long-term value: 1800 mg/m², 1000 ppm Cell (USA) Long-term value: 1800 mg/m², 1000 ppm Cell (USA) Long-term value: 1800 mg/m², 1000 ppm Cell (USA) Long-term value: 200 ppm BEI Celling Celling value: 300 mg/m², 1000 ppm Celli		nd emergency	Wear protective equipment. Keen upprotected persons away
Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Lee only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acctone PEL (USA) Long-term value: 590 mg/m ³ , 1000 ppm LUV (USA) Long-term value: 590 mg/m ³ , 250 ppm BEI 106-88-3 Toluene PEL (USA) Long-term value: 200 ppm BEI 106-98-5 Toluene PEL (USA) Long-term value: 200 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m ³ , 100 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m ³ , 1000 ppm TLV (USA) Long-term value: 1800 mg/m ³ , 1000 ppm TLV (USA) Long-term value: 200 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m ³ , 1000 ppm TLV (USA) Long-term value: 1900 mg/m ³ , 1000 ppm TLV (USA) Long-term value: 500 mg/T TLV (USA) Long-term value: 500 mg/T TLV (USA) Long-term v	•		Use respiratory protective device against the effects of fumes/dust/aerosol.
Dispose contaminated material as waste according to section 13. Handling and storage Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Accone PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm Long-term value: 594 mg/m³, 250 ppm BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 ppm Celling limit value: 300, 500° ppm 10-m peak per 8-hr shift TLV (USA) Long-term value: 200 ppm Celling limit value: 300, 500° ppm 10-m peak per 8-hr shift TLV (USA) Short-term value: 200 ppm 8EI, NLC-OTO TVV (USA) Long-term value: 300 mg/m³, 100 ppm 8EI, NLC-OTO TVV (USA) Long-term value: 300 mg/m³, 1000 ppm 8EI, NLC-OTO TVV (USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 1000 ppm 8EI, USA) Long-term value: 207 mg/m³, 1000 ppm 8EI, USA) Long-term value: 1800 mg/m³, 800 ppm 8EI, USA) Long-term value: 50 ppm 8EI (USA) Long-term value			
Precautions for safe handling Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection	containment	and cleaning up:	Dispose contaminated material as waste according to section 13.
Precautions for safe handling Storage requirements: Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acetome PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm Darg-term value: 1187 mg/m³, 500 ppm BEI Long-term value: 590 mg/m³, 250 ppm 108-88-3 Toluene Celling limit value: 300; 500° ppm *10-min peak pet 8-hr shift REL (USA) Long-term value: 200 ppm BEI, NIC-OTO PEL (USA) Long-term value: 300 gpm³, 100 ppm Long-term value: 300 gpm³, 100 ppm TUV (USA) Long-term value: 20 ppm BEI, NIC-OTO Rest, NIC-OTO 74-98-6 propane PEL PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm TUV (USA) Long-term value: 1800 mg/m³, 1000 ppm (EG), DAG-term value: 1800 mg/m³, 1000 ppm (EG) REL (USA) Long-term value: 1800 mg/m³, 1000 ppm (ES) Long-term value: 1800 mg/m³, 1000 ppm (ES) REL (USA) Long-term value: 1800 mg/m³, 1000 ppm (ES) Long-term value: 1800 mg/m³, 1000 ppm (ES) REL (USA) Long-term value: 1900 mg/m³, 1000 ppm (ES) Long-term value: 1800 mg/m³, 1000 ppm (ES) BEI (USA) Long-term value: 50 ppm Long-t	Handling ar	ad storago	
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditio Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acetone Components with limit values that require monitoring at the workplace: 67-64-1 Acetone Components with limit value: 2400 mg/m³, 250 ppm REL (USA) Long-term value: 590 mg/m³, 500 ppm Long-term value: 590 mg/m³, 500 ppm Celling limit value: 300; 500° ppm BEI Component with set of the soft 100-retrm value: 300; 500° ppm Celling limit value: 300; 500° ppm 10-min peak per 8-In soft Store locked up. PEL (USA) Long-term value: 300; 500° ppm 10-min peak per 8-In soft Stop ppm Celling limit value: 200 ppm Celling limit value: 300; 500° ppm 11-V (USA) Long-term value: 300 ppm Celling limit value: 300; 500° ppm 11-V (USA) Long-term value: 1800 mg/m³, 1000 ppm Celling limit value: 300; 500° ppm 12-V (USA) Long-term value: 1800 mg/m³, 1000 ppm Celling limit value: 300; 500° ppm 12-V (USA) Long-term value: 1800 mg/m³, 1000 ppm Celling limit value: 300; 500° ppm 12-V (USA) Long-term value: 200 ppm			Use only in well ventilated areas.
Store locked up. Exposure controls/personal protection Components with limit values that require monitoring at the workplace: G7-64-1 Acetone PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm BEI Components with limit value: 594 mg/m³, 250 ppm BEI Components walue: 1800 mg/m³, 250 ppm Long-term value: 594 mg/m³, 250 ppm Eugentary Long-term value: 594 mg/m³, 250 ppm Eugentary 108-88-3 Toluene Celling limit value: 300; 500° ppm *10-min peak per 8-hr shift Stort-ferm value: 375 mg/m³, 100 ppm Long-term value: 375 mg/m³, 100 ppm Eugentary Long-term value: 1800 mg/m³, 1000 ppm Eugentary TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Long-term value: 300 mg/m³, 1000 ppm TLV (USA) Long-term value: 300 pm/m³, 1000 ppm<		tor sate nandlind	
Components with limit values that require monitoring at the workplace: 67-64-1 Acetone PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm BEI 106-88-70 Toluene PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500° ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 560 mg/m³, 100 ppm TLV (USA) Short-term value: 200 ppm PEL (USA) Long-term value: 200 ppm PEL (USA) Long-term value: 200 ppm TLV (USA) Long-term value: 200 ppm REL (USA) Long-term value: 200 ppm REL (USA) Long-term value: 200 ppm PEL (USA) Long-term value: 200 ppm REL (USA) Long-term value: 200 ppm REL (USA) Long-term value: 200 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 200 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1900 mg/m³, 1000 ppm REL (USA) Long-term value: 1900 mg/m³, 1000 ppm REL (USA) Long-term value: 500 ppm TLV (USA) I Long-term value: 500 ppm REL (USA) Short-term value: 50 pp			
Components with limit values that require monitoring at the workplace: 67-64-1 Acctone FEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 594 mg/m³, 250 ppm Dang-term value: 1187 mg/m³, 250 ppm BEI Bort-term value: 200 ppm Dang-term value: 200 ppm BEI Dessert Toluene PEL (USA) Long-term value: 300, 500° ppm '10-min peak per 8-hr shift The may mg/m³, 100 ppm Cang-term value: 200 ppm Ceiling limit value: 20 ppm Deng-term value: 360 mg/m³, 150 ppm Cong-term value: 370 mg/m³, 100 ppm Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm Et (USA) Long-term value: 1800 mg/m³, 1000 ppm Et (USA) Long-term value: 1800 mg/m³, 1000 ppm Et (USA) Long-term value: 2370 mg/m³, 1000 ppm Et (USA) IDeng-term value: 1900 mg/m³, 800 ppm Its (USA) IDeng-term value: 2370 mg/m³, 1000 ppm Et (USA) IDeng-term value: 200 mg/m³, 1000 ppm Its (USA) IDeng-term value: 50 ppm Its (USA) Ingredients with biological lim			
67-64-1 Acetone PEL (USA) Long-term value: 2400 mg/m³, 250 ppm REL (USA) Long-term value: 1187 mg/m³, 500 ppm Dog-term value: 594 mg/m³, 250 ppm BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500° ppm *10-min peak per 8-hr shift Short-term value: 375 mg/m³, 100 ppm Long-term value: 375 mg/m³, 100 ppm Long-term value: 375 mg/m³, 100 ppm Long-term value: 200 ppm BEI, NIC-OTO PEL (USA) Long-term value: 375 mg/m³, 100 ppm PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm PEL (USA) IC6-97-6 n-butane PEL PEL REL (USA) Long-term value: 2370 mg/m³, 800 ppm PC TLV (USA) Short-term value: 200 mg/m³, 1000 ppm PC IC6-97-6 n-butane PE PC REL (USA) Long-term value: 2070 mg/m³, 800 ppm PC TLV (USA) Short-term value: 375 mg/m³, 1000 ppm FC IC6-97-6 PM acetate	Expeditor	lirements:	Store locked up.
PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm JNOT-term value: 594 mg/m³, 250 ppm BEI 108-88-3 Toluene PEL (USA) Cong-term value: 200 ppm Celling limit value: 300; 500° ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 375 mg/m³, 100 ppm Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) LONG-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) So mg/L Medi	-	irements: ontrols/personal pro	Store locked up. tection
REL (USA) Long-term value: 590 mg/m³, 250 ppm TLV (USA) Short-term value: 594 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500° ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 20 ppm BEI, NIC-OTO BEI, NIC-OTO PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 20 pm g/m³, 1000 ppm REL (USA) Long-term value: 370 mg/m³, 800 ppm Short-term value: 20 pm g/m³, 1000 ppm Impediately remove all soled Id6-97-8 n-butane Impediately remove all soled REL (USA) Long-term value: 300 mg/m³, 1000 ppm (EX) Long-term value: 20 pp mg/m³, 1000 ppm Impredients with biologi	Components	irements: ontrols/personal pro	Store locked up. tection
TLV (USA) Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm 108-88-3 Toluene PEL (USA) Long-term value: 200 ppm Celling limit value: 300; 500* ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 506 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV (USA) Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 2070 mg/m³, 800 ppm TLV (USA) Long-term value: 2370 mg/m³, 1000 ppm TLV (USA) Long-term value: 2370 mg/m³, 1000 ppm TLV (USA) Long-term value: 50 ppm Ingredients with biological limit values: Gr64-1 Acetone BEI (USA) Long-term value: 50 ppm Ingredients with biological limit values: Gr64-1 Acetone BEI (USA) Song/L Medium: urine Time: end of shift Paramete	Components 67-64-1 Aceto	irements: ontrols/personal pro with limit values that i one	Store locked up. tection require monitoring at the workplace:
Long-term value: 594 mg/m³, 250 ppm BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300, 500° ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 500 mg/m³, 150 ppm Long-term value: 275 mg/m³, 100 ppm Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Long-term value: 2370 mg/m³, 1000 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm KEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64 M acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64 1 Acetone BEI (USA) So mg/L Medium: urine Time: end of shift <	Components 67-64-1 Aceto PEL (USA)	irements: ontrols/personal pro with limit values that i one Long-term value: 2400	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm
BEI Image: Constraint of the second seco	Components 67-64-1 Aceto PEL (USA) REL (USA)	irements: ontrols/personal pro- with limit values that i one Long-term value: 2400 Long-term value: 590 m	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm
PEL (USA) Long-term value: 200 ppm	Components 67-64-1 Aceto PEL (USA) REL (USA)	irements: ontrols/personal pro with limit values that i one Long-term value: 2400 Long-term value: 590 m Short-term value: 1187	Store locked up. tection require monitoring at the workplace: mg/m ³ , 1000 ppm mg/m ³ , 250 ppm mg/m ³ , 500 ppm
Ceiling limit value: 300; 500° ppm *10-min peak per 8-hr shift REL (USA) Short-term value: 375 mg/m³, 100 ppm Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm LUX (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm TUV (USA) Iong-term value: 1900 mg/m³, 800 ppm Short-term value: 2370 mg/m³, 1000 ppm [EX] 106-97-8 n-butane Iong-term value: 2370 mg/m³, 1000 ppm TUV (USA) Short-term value: 2370 mg/m³, 1000 ppm [EX] Long-term value: 2370 mg/m³, 1000 ppm [EX] Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) So mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)	Components 67-64-1 Aceto PEL (USA) REL (USA)	irements: ontrols/personal pro with limit values that i one Long-term value: 2400 Long-term value: 590 m Short-term value: 1187 Long-term value: 594 m	Store locked up. tection require monitoring at the workplace: mg/m ³ , 1000 ppm mg/m ³ , 250 ppm mg/m ³ , 500 ppm
*10-min peak per 8-hr shift REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL REL (USA) Long-term value: 1900 mg/m³, 800 ppm (EX) 108-65-6 PM acetate Short-term value: 2370 mg/m³, 1000 ppm (EX) 108-65-6 PM acetate WEEL (USA) USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all solied and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 1187 Long-term value: 594 m BEI	Store locked up. tection require monitoring at the workplace: mg/m ³ , 1000 ppm ng/m ³ , 250 ppm mg/m ³ , 500 ppm
REL (USA) Short-term value: 506 mg/m³, 100 ppm Long-term value: 375 mg/m³, 100 ppm BEI, NIC-OTO 74.98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) Long-term value: 1800 mg/m³, 1000 ppm refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 mg/m³, 800 ppm (EX) 106-97-8 n-butane Short-term value: 2370 mg/m³, 1000 ppm (EX) 108-65-6 PM acetate WEEL (USA) 109-ferm value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m BEI uene Long-term value: 200 p	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm mg/m³, 250 ppm mg/m³, 250 ppm pm
Long-term value: 375 mg/m³, 100 ppm TLV (USA) Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane RE REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm TLV (USA) Long-term value: 500 ppm Ide-56-6 PM acetate Meetu WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300;	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm ng/m³, 250 ppm pm 500* ppm
TLV (USA) Long-term value: 20 ppm BEI, NIC-OTO 74-98-6 propure PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) So mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 1187 Long-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm pm 500* ppm shift
BEI, NIC-OTO 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm [EX] Short-term value: 2370 mg/m³, 1000 ppm [EX] Iong-term value: 2370 mg/m³, 1000 ppm [EX] Short-term value: 2370 mg/m³, 1000 ppm [EX] Short-term value: 2370 mg/m³, 1000 ppm [EX] Short-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) So mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA)	ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 560 n	Store locked up. tection require monitoring at the workplace: mg/m ³ , 1000 ppm ng/m ³ , 250 ppm mg/m ³ , 500 ppm pm 500* ppm shift ng/m ³ 150 ppm
PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L. Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 560 m Long-term value: 375 m	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm pm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) Short-term value: 2370 mg/m³, 1000 ppm 108-65-6 PM acetate WEEL (USA) WEEL (USA) Long-term value: 50 ppm 1ngredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Acete PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm pm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm
TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) Short-term value: 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Acete PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 500 ppm ng/m³, 250 ppm ng/m³, 250 ppm ng/m³, 150 ppm ng/m³, 150 ppm ng/m³, 100 ppm ng/m³, 100 ppm ng/m³, 100 ppm
106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Acete PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 360 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800	Store locked up.
REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA)	irements: ontrols/personal pro- with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800	Store locked up.
TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) TLV (USA)	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI Long-term value: 594 m BEI Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTl	Store locked up.
IQ8-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) TLV (USA) 106-97-8 n-bu	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 360 n Long-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTl utane	Store locked up. The store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm mg/m³, 250 ppm mg/m³, 500 ppm mg/m³, 250 ppm pm : 500* ppm : 500* ppm shift ng/m³, 150 ppm mg/m³, 100 ppm mg/m³, 100 ppm mg/m³, 100 ppm mg/m³, 1000 ppm LVs&BEIs book; D, EX
108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) 106-97-8 n-bu REL (USA)	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTI utane Long-term value: 1900	Store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 500 ppm ig/m³, 250 ppm pm * 500* ppm shift ng/m³, 150 ppm mg/m³, 150 ppm mg/m³, 150 ppm mg/m³, 1000 ppm LVs&BEIs book; D, EX
Ingredients with biological limit values: 67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) 106-97-8 n-bu REL (USA)	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTI utane Long-term value: 1900 Short-term value: 2370	Store locked up. The store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm mg/m³, 250 ppm ng/m³, 500 ppm mg/m³, 250 ppm pm store locked up. pm store locked up. pm mg/m³, 150 ppm ng/m³, 150 ppm mg/m³, 150 ppm ng/m³, 150 ppm mg/m³, 100 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm
67-64-1 Acetone BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTI utane Long-term value: 1900 Short-term value: 2370 (EX) acetate	Store locked up.
BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA)	ontrols/personal provements: ontrols/personal provements with limit values that is one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 300 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTl utane Long-term value: 2370 (EX) acetate Long-term value: 50 pp	Store lockéd up. - tection - require monitoring at the workplace: - mg/m³, 1000 ppm - ng/m³, 500 ppm - ng/m³, 250 ppm - ng/m³, 250 ppm - ng/m³, 250 ppm - ng/m³, 150 ppm - ng/m³, 100 ppm - mg/m³, 100 ppm - mg/m³, 1000 ppm - mg/m³, 800 ppm - mg/m³, 1000 ppm - m - m - m - m - m - m<
Medium: urine Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 20 pp BEI, NIC-OTO ane Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Icong-term value: 1800 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val	Store lockéd up. - tection - require monitoring at the workplace: - mg/m³, 1000 ppm - ng/m³, 500 ppm - ng/m³, 250 ppm - ng/m³, 250 ppm - ng/m³, 250 ppm - ng/m³, 150 ppm - ng/m³, 100 ppm - mg/m³, 100 ppm - mg/m³, 1000 ppm - mg/m³, 800 ppm - mg/m³, 1000 ppm - m - m - m - m - m - m<
Time: end of shift Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceto PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v 67-64-1 Aceto	irements: ontrols/personal provements with limit values that is one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 300 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 20 pp BEI, NIC-OTO ane Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Icong-term value: 1800 Short-term value: 1800 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit valuents one	Store lockéd up. - tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 500 ppm ng/m³, 250 ppm ng/m³, 250 ppm ng/m³, 250 ppm mg/m³, 150 ppm ng/m³, 100 ppm mg/m³, 100 ppm mg/m³, 100 ppm mg/m³, 1000 ppm mg/m³, 800 ppm mg/m³, 1000 ppm
Parameter: Acetone (nonspecific) Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Acete PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v 67-64-1 Acete BEI (USA) 50	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 300; *10-min peak per 8-hr s Short-term value: 300 p Ceiling limit value: 300 p Ceiling limit value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Long-term value: 1800 Icong-term value: 1800 Short-term value: 1900 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val one D mg/L	Store lockéd up. - tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 500 ppm ng/m³, 250 ppm ng/m³, 250 ppm ng/m³, 250 ppm ng/m³, 150 ppm ng/m³, 100 ppm mg/m³, 100 ppm mg/m³, 100 ppm mg/m³, 1000 ppm mg/m³, 800 ppm mg/m³, 1000 ppm
Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceta PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) 108-65-6 PM WEEL (USA) SM 67-64-1 Aceta BEI (USA)	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTI utane Long-term value: 1900 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val one) mg/L edium: urine	tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm pm '500* ppm shift ng/m³, 150 ppm ng/m³, 100 ppm m m mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 800 ppm mg/m³, 800 ppm mg/m³, 1000 ppm
Immediately remove all soiled and contaminated clothing. Wash hands after use.	Components 67-64-1 Aceta PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v 67-64-1 Aceta BEI (USA) Tu	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 375 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 refer to Appendix F inTI utane Long-term value: 1900 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val one 0 mg/L edium: urine me: end of shift	Store locked up. The store locked up. tection require monitoring at the workplace: mg/m³, 1000 ppm mg/m³, 250 ppm ng/m³, 250 ppm mg/m³, 250 ppm '500° ppm shift ng/m³, 150 ppm mg/m³, 150 ppm mg/m³, 100 ppm mg/m³, 100 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 800 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm mg/m³, 1000 ppm
Wash hands after use.	Components 67-64-1 Aceta PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v 67-64-1 Aceta BEI (USA) TU	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 360 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Long-term value: 1800 cong-term value: 1800 Short-term value: 1800 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val one) mg/L edium: urine me: end of shift arameter: Acetone (nons	Store locked up. Testion require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm mg/m³, 250 ppm pm 550° ppm /500° ppm ng/m³, 150 ppm ng/m³, 1000 ppm ng/m³, 1000 ppm mg/m³, 1000 ppm ng/m³, 1000 ppm mg/m³, 1000 ppm ng/m³, 1000 ppm mg/m³, 1000 ppm ng/m³, 1000 ppm uses: ng/m³, 1000 ppm ppecific) b
(Contd. on pag	Components 67-64-1 Aceta PEL (USA) REL (USA) TLV (USA) 108-88-3 Tolu PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 74-98-6 propa PEL (USA) REL (USA) TLV (USA) 106-97-8 n-bu REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) Ingredients v 67-64-1 Aceta BEI (USA) TU	irements: ontrols/personal provements with limit values that in one Long-term value: 2400 Long-term value: 590 m Short-term value: 594 m BEI uene Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s Short-term value: 360 m Long-term value: 375 m Long-term value: 20 pp BEI, NIC-OTO ane Long-term value: 1800 Long-term value: 1800 Long-term value: 1800 cong-term value: 1800 Short-term value: 1800 Short-term value: 2370 (EX) acetate Long-term value: 50 pp with biological limit val one) mg/L edium: urine me: end of shift arameter: Acetone (nons	Store lockéd up. tection require monitoring at the workplace: mg/m³, 1000 ppm ng/m³, 250 ppm ng/m³, 250 ppm js0/m³, 250 ppm ng/m³, 250 ppm ng/m³, 150 ppm ng/m³, 100 ppm mg/m³, 1000 ppm uvs&BEIs book; D, EX mg/m³, 1000 ppm me ues: pecific) Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing.

Page 3/4

Trade name: LIGHT GRAY	
	(Contd. of page 2) Avoid contact with the eyes and skin.
Breathing equipment:	Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance: Odor: Odor threshold:	Aerosol. Aromatic Not determined.
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)
Flash point: Flammability (solid, gas):	Not applicable, as aerosol. Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water:	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. Not determined.
Solubility: Viscosity: Water:	Not determined. Not determined. 0.0 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing
	temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:		
108-65-6 PM acetate		
Oral LD50 8,500 mg/kg (ra	at)	
Inhalative LC50/4 h 35.7 mg/l (rat)		
Information on toxicological effect	t s: No data available.	
Skin effects:	Irritant to skin and mucous membranes.	
Eye effects:	Irritating effect.	
Sensitization:	No sensitizing effects known.	
12 Ecological information	Hazardaua far watar, da pat amptu into draino	
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.	
Bioaccumulative potential:	No further relevant information available.	
Mobility in soil:	No further relevant information available.	
Other adverse effects:	No further relevant information available.	
13 Disposal considerations Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be		

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

늗

F

Revised On 10/14/2021

Trade name: LIGHT GRAY		
Recommended cleansing agent:	(Contd. of page 3) (Contd. of page 3)	
14 Transport information		
UN-Number DOT	UN1950 UN1950	
DOT	UN1950 DOT Aerosols, flammable	
ADR Transport hazard class(es): Class Marine pollutant:	1950 Aerosols 2.1 No	
Special precautions for user: EMS Number:	Warning: Gases F-D,S-U	
Packaging Group: UN "Model Regulation":	 UN1950, Aerosols, 2.1	
15 Regulatory information		
SARA Section 355 (extremely hazar		
None of the ingredients in this produc		
SARA Section 313 (Specific toxic c	hemical listings):	
108-88-3 Toluene Toxic Substances Control Act		
(TSCA):	All hazardous ingredients are found on the inventory list of substances.	
Canadian Domestic Substances Lis (DSL): Consumer Product Safety	All ingredients are listed or exempted.	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals	s known to cause cancer:	
13463-67-7 titanium dioxide		
Prop 65 chemicals known to cause	birth defects or reproductive harm:	
108-88-3 Toluene		
EPA: 67-64-1 Acetone	1	
16 Other information		
Contact:	Regulatory Affairs	