

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

## 1 Identification

- **Product identifier**
- **Trade name:** Super Wheel Brightener
- **Article number:** C-33
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **Details of the supplier of the safety data sheet**

---

- **Manufacturer/Supplier:**  
BAF Industries  
8010 Dixie Highway  
Florence, KY 41042 USA  
Phone: 859-372-5900
- **Information department:** sds\_info@prowax.com
- **Emergency Telephone Number:** ChemTrec: 800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



Skull and crossbones

Toxic if swallowed.



Corrosion

Causes severe skin burns and eye damage.

Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard statements**  
Toxic if swallowed.  
Causes severe skin burns and eye damage.
- **Precautionary statements**  
Do not breathe dusts or mists.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If swallowed: Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
If swallowed: Rinse mouth. Do NOT induce vomiting.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Wash contaminated clothing before reuse.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### · **Dangerous components:**

1341-49-7	ammonium bifluoride	10-25%
127087-87-0	surfactant	≤2.5%

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Do not induce vomiting; immediately call for medical help.  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.  
· **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Use neutralizing agent.  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
 The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.
- **Breathing equipment:**  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 3)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

\*

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Dark purple
Odor:	Odorless
Odor threshold:	Not determined.

· **pH-value at 20 °C (68 °F):** 3

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1.0437 g/cm<sup>3</sup> (8.7097 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 4)

- |                                     |  |
|-------------------------------------|--|
| · <b>Viscosity:</b>                 |  |
| <b>Dynamic:</b>                     | Not determined                             |
| <b>Kinematic at 40 °C (104 °F):</b> | <20.5 mm <sup>2</sup> /s                   |
| · <b>Solvent content:</b>           |  |
| <b>Water:</b>                       | 83.3 %                                     |
| <b>VOC content:</b>                 | 0.00 %                                     |
| · <b>Solids content:</b>            |  |
|                                     | 16.6 %                                     |
| · <b>Other information</b>          |  |
|                                     | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**  
Strong caustic effect.  
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Toxic  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

### · IARC (International Agency for Research on Cancer)

1341-49-7 ammonium bifluoride

3

### · NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USA

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 5)


## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 1 (Self-assessment): slightly hazardous for water*  
*Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.*  
*Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |   |  |
|---|--|
| · <b>UN-Number</b>  | UN3264   |
| · <b>DOT, ADR, IMDG, IATA</b>   |  |
| · <b>UN proper shipping name</b>  | Corrosive liquid, acidic, inorganic, n.o.s. (Ammonium hydrogendifluoride)      |
| · <b>DOT</b>  | 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (AMMONIUM HYDROGENDIFLUORIDE) |
| · <b>ADR</b>  | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (AMMONIUM HYDROGENDIFLUORIDE)      |
| · <b>IMDG, IATA</b>   |  |
| · <b>Transport hazard class(es)</b>   |  |
| · <b>DOT</b>  |  |
|  |  |
| · <b>Class</b>  | 8 Corrosive substances   |

(Contd. on page 7)

USA

# Safety Data Sheet


acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 6)

· <b>Label</b>	8
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Corrosive substances
· <b>Hazard identification number (Kemler code):</b>	80
· <b>EMS Number:</b>	F-A,S-B
· <b>Segregation groups</b>	Acids
· <b>Stowage Category</b>	B
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (AMMONIUM HYDROGENDIFLUORIDE), 8, II

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

127087-87-0 surfactant

- TSCA (Toxic Substances Control Act) All ingredients are listed

(Contd. on page 8)

USA



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 7)

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

1341-49-7 ammonium bifluoride

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**· **Signal word** Danger· **Hazard statements**

Toxic if swallowed.

Causes severe skin burns and eye damage.

· **Precautionary statements**

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/30/2021

Reviewed on 04/30/2021

Trade name: Super Wheel Brightener

(Contd. of page 8)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Contact:**

· **Date of preparation / last revision** 04/30/2021 / 16

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

· **\* Data compared to the previous version altered.**

USA