Printing date 10/15/2021 Reviewed on 10/15/2021

1 Identification

· Product identifier

· Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

· Article number: P-27-Q

· Application of the substance / the mixture Polishing agent/ Burnishing compound

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

BAF Industries 8010 Dixie Highway Florence, KY 41042 USA Phone:859-372-5900

· Information department: sds_info@prowax.com

Emergency Telephone Number: ChemTrec: 800-424-9300 Outside USA 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flammable liquid and vapor.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

USA

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous co	omponents:	
64742-47-8	Distillates (petroleum), hydrotreated light	10-25%
64742-88-7	medium aliphatic hydrocarbon	2.5-10%
112926-00-8	Precipitated silica (Silica-Amorphous)	2.5-10%
61790-12-3	tall oil fatty acids Consisting of: 112-80-1 oleic acid, pure (≥0-≤50%); 60-33-3 linoleic acid, pure (≥0-≤50%)	<i>≤</i> 2.5%
102-71-6	Triethanolamine	<i>≤</i> 2.5%

4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

(Contd. of page 2)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112926-00-8 Precipitated silica (Silica-Amorphous)

PEL 20mppcf or 80mg/m3 /%SiO2
REL Long-term value: 6 mg/m³
See Pocket Guide App. C

TLV TLV withdrawn

102-71-6 Triethanolamine

TLV Long-term value: 5 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 4)

USA

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

· Material of gloves

(Contd. of page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

α		, ,				
- U P	DUCTON	and	chami	Cal	nrai	novitano
7	hysical	ME EN EN EN				
			01001100		$P - \cup_{k}$	

Information on basic physical and c	hemical properties
· General Information	
· Appearance:	T · · · 1
Form:	Liquid
Color:	Whitish
Odor:	Solvent-like
· Odor threshold:	Not determined.
· pH-value at 20 °C (68 °F):	9.1
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	60 °C (140 °F)
· Flash point:	42 °C (107.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	210 °C (410 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.8 Vol %
Upper:	6 Vol %
· Vapor pressure at 20 °C (68 °F):	2 hPa (1.5 mm Hg)
· Density at 20 °C (68 °F):	1.1503 g/cm³ (9.5993 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.

(Contd. on page 5)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

		(Contd. of page 4
· Viscosity:		
Dynamic at 20 °C (68 °F):	13,000 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	25.1 %	
Water:	36.1 %	
VOC content:	11.90 %	
Solids content:	39.8 %	
• Other information No further relevant information available.		

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
64742-88-	64742-88-7 medium aliphatic hydrocarbon		
Oral	LD50	>6,500 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
Inhalative	LC50/4 h	>14 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

Caremogenic caregories	
· IARC (International Agency for Research on Cancer)	
112926-00-8 Precipitated silica (Silica-Amorphous)	
102-71-6 Triethanolamine	-
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administra	ution)
None of the ingredients is listed.	

USA

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
$\cdot DOT$	NA1993
· ADR, IMDG, IATA	UN1993

· UN proper shipping name

· **DOT**COMBUSTIBLE LIQUID, N.O.S (medium aliphatic hydrocarbon)

· **ADR**1993 FLAMMABLE LIQUID, N.O.S.

· **IMDG**FLAMMABLE LIQUID, N.O.S.

· IATA FLAMMABLE LIQUID, N.O.S. (medium aliphatic hydrocarbon)

- · Transport hazard class(es)
- $\cdot DOT$



Class 3 Combustible liquids

(Contd. on page 7)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

	(Contd. of page
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	III
	III
Environmental hazards: Marine pollutant:	No
<u> </u>	
Special precautions for user Hazard identification number (Kemler code)	Warning: Flammable liquids: 30
EMS Number:	<i>F-E,S-E</i>
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
100	On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1
Excepted quantumes (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1 aluminium oxide

52-51-7 bronopol (INN)

· TSCA (Toxic Substances Control Act) All ingredients are listed

(Contd. on page 8)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

(Contd. of page 7)

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

1344-28-1 aluminium oxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 10/15/2021 / 49

(Contd. on page 9)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: ULTIMATE CUTTER & SCRATCH REMOVER

(Contd. of page 8)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

* * Data compared to the previous version altered.

USA ·