Printing date 10/15/2021 Reviewed on 10/15/2021

1 Identification

· Product identifier

· Trade name: POLY GARD PAINT SEALANT

· Article number: P-63

· Application of the substance / the mixture Lustre

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

BAF Industries 8010 Dixie Highway Florence, KY 41042 USA Phone:859-372-5900

· Information department: sds_info@prowax.com

Emergency Telephone Number: ChemTrec: 800-424-9300 Outside USA 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flammable liquid and vapor.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

US.

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
64742-88-7	medium aliphatic hydrocarbon	10-25%
64742-47-8	Distillates (petroleum), hydrotreated light	
1332-58-7	Kaolin	2.5-10%

4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

(Contd. of page 2)

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 2* mg/m³
E; as respirable fraction, A4

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

(Contd. of page 3)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	
Information on basic physical and c	hemical properties
General Information	
Appearance:	I::J
Form: Color:	Liquid Light blue
· Odor:	Fruit-like
· Ouor: · Odor threshold:	Not determined.
pH-value at 20 °C (68 °F):	9
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	42 °C (107.6 °F)
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	265 °C (509 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	0.8 Vol %
Upper:	6 Vol %
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	0.9766 g/cm³ (8.1497 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	15,000 mPas
Kinematic:	Not determined.

(Contd. on page 5)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

 Solvent content:
 (Contd. of page 4)

 Organic solvents:
 20.8 %

 Water:
 62.6 %

 VOC content:
 14.24 %

 139.0 g/l / 1.16 lb/gal

 Solids content:
 10.6 %

 • Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-88-7 medium aliphatic hydrocarbon

Oral	LD50	>6,500 mg/kg (rat)
	LD50	>3,000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (Inte	· IARC (International Agency for Research on Cancer)		
67-63-0	propan-2-ol	3	
98-82-8	cumene	2B	
	ethylbenzene	2B	
14808-60-7	silica	1	

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USA

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
$\cdot DOT$	NA1993
· ADR, ADN	Void
IMDG, IATA	UN1993

· UN proper shipping name

• DOT COMBUSTIBLE LIQUID, N.O.S (medium aliphatic hydrocarbon,

Isopropanol)

· ADR, ADN Void

· IMDG FLAMMABLE LIQUID, N.O.S.

· IATA FLAMMABLE LIQUID, N.O.S. (medium aliphatic hydrocarbon,

ISOPROPANOL (ISOPROPYL ALCOHOL))

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Combustible liquids

· Label 3

(Contd. on page 7)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

	(Contd. of page
· ADR, ADN	
· Class	Void
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IATA	III
· ADR, IMDG	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· EMS Number:	F-E, <u>Š-E</u>
· Transport in bulk according to Annex II o	f
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
·DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
-	On cargo aircraft only: 220 L
· UN ''Model Regulation'':	Void

15 Regulatory information

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$
- ·Sara

· Section 35	55 (ext	remely	hazardous	substances):
M 41.	:	- 1:4	:- 1:-4-1	

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

67-56-1	methanol
98-82-8	cumene
100-41-4	ethylbenzene
52-51-7	bronopol (INN)

67-63-0 propan-2-ol

· TSCA (Toxic Substances Control Act) All ingredients are listed

· Hazardo	us Air Pollutants
67-56-1	methanol
98-82-8	cumene
100-41-4	ethylbenzene

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 8)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

Contd. of page 7)

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

67-56-1 methanol

· EPA (Envir	conmental Protection Agency)		
98-82-8 c	umene	D, Cl	BD
100-41-4 e	thylbenzene	D	
· TLV (Thres	hold Limit Value)		
1332-58-7	Kaolin		A4
67-63-0	propan-2-ol		A4
100-41-4	ethylbenzene		A3
14808-60-7	silica		A2
· NIOSH-Ca	(National Institute for Occupational Safety and Health)		
14808-60-7	silica		

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- Date of preparation / last revision 10/15/2021 / 21

(Contd. on page 9)

Printing date 10/15/2021 Reviewed on 10/15/2021

Trade name: POLY GARD PAINT SEALANT

(Contd. of page 8)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3

* * Data compared to the previous version altered.