Printing date 01/20/2021 Reviewed on 06/03/2020

### 1 Identification

· Product identifier

· Trade name: ALLURA FINAL FINISH WAX

· Article number: P-9-Q

· Application of the substance / the mixture Lustre

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

BAF Industries 8010 Dixie Highway Florence, KY 41042 USA Phone:859-372-5900

· Information department: sds\_info@prowax.com

Emergency Telephone Number: ChemTrec: 800-424-9300 Outside USA 703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



Flammable liquid and vapor.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

US.

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

(Contd. of page 1)

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
64742-88-7	medium aliphatic hydrocarbon	10-25%
64742-47-8	Distillates (petroleum), hydrotreated light	10-25%
1332-58-7	Kaolin	2.5-10%
	tall oil fatty acids Consisting of: 112-80-1 oleic acid, pure (≥0-≤50%); 60-33-3 linoleic acid, pure (≥0-≤50%)	≤2.5%

## 4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

See Section 13 for disposal information.

(Contd. of page 2)

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m³ E; as respirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

(Contd. of page 3)

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

$\alpha$ $\mathbf{n}$	•					
	NOTON	$\alpha n \alpha$	0.000	Cal	nra	perties
	AWATIONIA	<b> </b>	i ka i i i i			
			 -		P - 0	P

<ul> <li>Information on basic physical and cl</li> <li>General Information</li> <li>Appearance:</li> </ul>	hemical properties
Form:	Viscous
Color:	Yellow
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value at 20 °C (68 °F):	9.7
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	42 °C (107.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	210 °C (410 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.8 Vol %
Upper:	6 Vol %
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	0.9346 g/cm³ (7.7992 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.

(Contd. on page 5)

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

		(Contd. of page 4
Viscosity:		
Dynamic at 20 °C (68 °F):	13,000 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	26.8 %	
Water:	48.6 %	
VOC content:	13.62 %	
	127.3 g/l / 1.06 lb/gal	
Solids content:	18.5 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
64742-88-	7 medium	aliphatic hydrocarbon	
		>6,500 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
		>14 mg/l (rat)	

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
14808-60-7 silica	1
· NTP (National Toxicology Program)	
14808-60-7 silica	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

-USA

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

(Contd. of page 5)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· UN-Number	
$\cdot DOT$	NA1993
· ADR, IMDG, IATA	UN1993

· UN proper shipping name

• DOT COMBUSTIBLE LIQUID, N.O.S (medium aliphatic hydrocarbon)
• ADR 1993 FLAMMABLE LIQUID, N.O.S. (medium aliphatic hydrocarbon)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (medium aliphatic hydrocarbon)

- · Transport hazard class(es)
- $\cdot DOT$



Class 3 Combustible liquids

(Contd. on page 7)

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

	(Contd. of pag
Label	3
ADR, IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 30 F-E, <u>S-E</u> A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (MEDIUM ALIPHAT HYDROCARBON), 3, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- · Section 313 (Specific toxic chemical listings):
- 52-51-7 bronopol (INN)
- · TSCA (Toxic Substances Control Act) All ingredients are listed
- · Hazardous Air Pollutants

None of the ingredients is listed.

(Contd. on page 8)

Printing date 01/20/2021 Reviewed on 06/03/2020

Trade name: ALLURA FINAL FINISH WAX

(Contd. of page 7)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

1332-58-7	Kaolin	A4
14808-60-7	silica	A2

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 silica

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: msds info@bafindustries.com
- · Date of preparation / last revision 01/20/2021 / 39

(Contd. on page 9)

Printing date 01/20/2021 Reviewed on 06/03/2020

#### Trade name: ALLURA FINAL FINISH WAX

(Contd. of page 8)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

\* Data compared to the previous version altered.

LISA